

## Product Features

Available in standard and custom configuration  
Tempered safety glass  
Full length magnetic closure  
Trouble free nylon pivot bushings  
Pivot side adjustment is  $\pm 3/4$   
Tapered drip trough with vinyl to channel  
water back inside the shower when  
the door is open

## Options

Glass patterns  
Finish



## Calculations

Maximum allowable width of unit = 37 (@ 72 tall)  
Maximum allowable height of unit = 84 (@ 30 wide)

## Glass Size

Width = Unit width - 3 5/8  
Height = Unit ht. - 3 1/2

## Metal Cuts

SC-551 strike jamb = Unit ht. - 1  
SC-549 strike rail = Unit ht. - 1 1/2  
SC-589 drip rail = SC-899 bottom rail - 11/16  
SC-621 pivot jamb = Unit ht. - 7/16  
SC-899 top & bottom rails = Unit width - 1 3/4  
SC-900 pivot rail = Unit ht. - 1 1/2  
SC-915 curb (optional) = Unit width

## Parts List

- A. 1 Curb
- B. 1 Jamb Wiper Vinyl
- C. 1 Pivot Jamb
- D. 2 Pivot Brackets
- E. 3 #6 x 3/8 Truss Head Screws
- F. 2 #8 x 1/8 Allen Set Screws
- G. 1 Allen Wrench (5/64)
- H. 6 Plastic Wall Anchors
- J. 3 #8 x 2 Truss Head Screws
- K. 2 #10 x 7/16 Sq. Head Set Screws
- L. 1 Glazed Door Panel
- M. 2 Nylon Pivot Bushings
- N. 1 Strike Jamb (Magnetic)
- P. 3 #8 x 1 1/2 Flat Head Screw
- R. 1 Interior Door Handle
- S. 1 Exterior Door Handle
- T. 2 #6 x 1 1/4 Round Head Screws
- V. 1 Drip Rail
- W. 1 Tapered Drip Vinyl
- X. 2 Drip Plugs
- Y. 1 Roll of Double Stick Tape

