



ROMAN TUB/WHIRLPOOL FAUCET TRIM

- Classic Series
- Two Handle Roman Tub Faucet
- Three Hole Installation
- Complete Trim and Rough-In

STANDARD SPECIFICATIONS:

- Solid fabricated brass end valves and spout body.
- Fixed 10" (254 mm) widespread mount on deck or ledge.
- 7 1/2" (191 mm) long, 5 3/16" (132 mm) high slip-on rigid spout.
- Conventional rough-in adjusts to 1 1/4" (32 mm) maximum deck thickness.
- 5/8" I.D. copper inlet supply tubes.
- Two-handle Roman Tub faucet for concealed mounting.
- Includes clear knob handles.
- Control mechanism is a rotating cylinder type with stainless steel plate and 180° rotation, with replaceable non-metallic seats operating in stainless steel lined sockets.
- Hot and cold stems are interchangeable.
- Temperature and volume controlled with handles.
- All operating parts shall be replaced from the top.


WARRANTY

- Lifetime Faucet and Finish Limited Warranty to the original consumer purchaser to be free from defects in material and workmanship.
- 5 Year Limited Warranty for usage in all industrial, commercial and business applications.



COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- CSA Certified





55 E. 111th Street, Indianapolis, IN 46280 395 Matheson Blvd. E., Mississauga, ON L4Z 2H2 © 2006 Masco Corporation of Indiana