




Location:




SYMMONS® Museo™

Tub-Shower System 5302

Specification Submittal



Feature Highlights

- Symmons Tub-Shower System with lever handles
- Symmons Temptrol® pressure-balancing mixing valve with adjustable stop screw to limit handle turn
- Showerhead #532SH single mode
- Showerhead mounting bracket and flange
- Standard flow rate is 2.5 gpm (9.5 L/min)
Optional lower flow rate restrictor available 
- Tub spout with diverter, # 532TSD
- Polished chrome finish

Model Numbers

- 5302
Tub-Shower System with Symmons Temptrol® pressure-balancing mixing valve p/n 4000-BODY
- 5302-TRM
Trim only, mixing valve ordered separately
- 4000-BODY
Symmons Temptrol® mixing valve without trim
- 4000-X-BODY
Symmons Temptrol® mixing valve without trim. Valve includes integral service stops to allow water shut-off for service

Finish Options / Modifications

Append appropriate -suffix to model number



- STN Satin nickel
- BLK Polished graphite
 - Polished chrome (standard finish)

Warranty

- Limited Lifetime - to the original end purchaser in consumer installations
- 5 years - for commercial installations

Options / Modifications

Append appropriate -suffix to model number

- IPS 1/2 inch female IPS connections on Symmons Temptrol® mixing valve
- X Symmons Temptrol® mixing valve includes integral service stops to allow water shut-off for service, p/n 4000-X-BODY. (Option only applies when ordering model 5302)
- REV Reverse coring in valve for back to back installations; hot on right, cold on left, (available with (-X) integral stops only)
- L/HD Showerhead not included. (Includes showerhead arm and flange only)
-  -2.0 2.0 (7.6 L/min) flow rate restrictor
-  -1.5 1.5 (5.7 L/min) flow rate restrictor

Standards / Certifications

ASME A112.18.1-2005/CSA B125.1-05

