

Location:



Tub-Shower & Hand Shower System 5406 Specification Submittal



Feature Highlights

- Symmons Tub-Shower & Hand Shower System with lever handles
- Symmons Temptrol® pressure-balancing mixing valve with adjustable stop screw to limit handle turn
- Separate triple outlet diverter valve with lever handle
- Showerhead #402SH2, three mode, 7-1/2 inch diameter
- Showerhead mounting bracket and flange
- Wall/hand shower #512HS, single mode with 5 foot flexible metal hose, in-line vacuum breaker, wall connection and cradle for hand shower mounting
- Standard flow rate is 2.5 gpm (9.5 L/min)
Optional lower flow rate restrictor available
- Tub spout, #542TS
- Polished chrome finish (standard)

Model Numbers

- 5406
Tub-Shower and Hand Shower System with Symmons Temptrol® mixing valve, p/n 4000-BODY and triple outlet diverter, p/n 4-460E-BODY
- 5406-TRM
Trim only, valve and diverter ordered separately
- 4000-BODY
Symmons Temptrol® mixing valve without trim
- 4000-X-BODY
Symmons Temptrol® mixing valve without trim. Valve includes integral service stops to allow water shut-off for service
- 4-460E-BODY
Symmons triple outlet diverter valve without trim

Finish Options / Modifications

Append appropriate -suffix to model number

- STN Satin Nickel
- ORB Oil Rubbed Bronze
- Polished Chrome (standard finish)

Options / Modifications

Append appropriate -suffix to model number

- IPS 1/2 inch female IPS connections on Symmons Temptrol® mixing valve
- X Integral service stops included with Temptrol mixing valve to allow water shut-off for service, p/n 4000-X-BODY (*Option only applies when ordering model 5406*)
- REV Reverse coring in valve for back to back installations; hot on right, cold on left, (*only available with -X integral service stops*)
- 2.0 2.0 (7.6 L/min) flow rate restrictor
- 1.5 1.5 (5.7 L/min) flow rate restrictor
- L/HD Showerhead not included (*includes showerhead arm and flange only*)
- L/HS Hand Shower wand not included (*includes hose, in-line vacuum breaker, wall connections and flange only*)
- 72 6 foot flexible metal hose in place of 5 foot
- R60 5 foot vinyl hose in place of flexible metal hose
- R72 6 foot vinyl hose in place of flexible metal hose
- QD Quick-disconnect at hand shower wall connection

Standards / Certifications


ASME A112.18.1-2005/CSA B125.1-05

Warranty

- Limited Lifetime - to the original end purchaser in consumer installations
- 5 years - for commercial installations

Dimensions Degas Tub-Shower & Hand Shower System, 5406

Male 1/2" I.P.S. thread must protrude 3/8" (10mm) from finished wall for proper installation of wall ell and cradle.



Note: Dimensions subject to change without notice