

Tub-Shower Valve System S-5400TS **Specification Submittal**

Feature Highlights

- Symmons Tub-Shower Valve System with lever handle
- Symmons Temptrol[®] pressure-balancing mixing valve with adjustable stop screw to limit handle turn
- Secondary integral diverter control handle
- Polished chrome finish



Model Numbers

S-5400TS Tub-Shower Valve System with Symmons Temptrol® mixing valve p/n S-4002-BODY
S-5400TS-TRM Trim only, mixing valve ordered separately
S-4002-BODY Symmons Temptrol [®] mixing valve without trim
S-4002-X-BODY Symmons Temptrol [®] mixing valve without trim. Valve includes integral service stops to allow water

Finish Options / Modifications

Append appropriate -suffix to model number

☐ -STN Satin Nickel

shut-off for service

- ☐ -ORB Oil Rubbed Bronze
 - Polished Chrome (standard finish)

Options / Modifications

Append appropriate -suffix to model number

- ☐ -IPS 1/2 inch female IPS connections on Symmons Temptrol® mixing valve (not available with -X integral service stops)
- -X Intergral service stops included with

 Temptrol® mixing valve to allow water
 shut-off for service, p/n S-4002-X-BODY
 (option only applies when ordering model
 S-5400TS)
- □ -REV Reverse coring in valve for back to back installations; hot on right, cold on left (only available with -X integral service stops)

Standards / Certifications

ASME A112.18.1-2005/CSA B125.1-05

Warranty

- Limited Lifetime to the original end purchaser in consumer installations
- 5 years for commercial installations

Dimensions Degas Tub-Shower Valve System, S-5400TS shower discharge 5/8" 16mm finished wall— 3 1/2"±1/2" ø7" 89mm±13mm 178mm use supplied plug in tub outlet for 2 3/8"±1/2" shower-only 60mm±13mm application hot and -cold inlets 6mm

Note: Dimensions subject to change without notice

