




SYMMONS® Temptrol® II 2000 Series

the smart choice™

Every Symmons Temptrol® II tub and shower system features the legendary Symmons Temptrol® pressure-balancing mixing valve. Constructed of solid brass, bronze and stainless steel, and featuring a piston that adjusts automatically to instantly and continually equalize or “balance” the hot and cold water pressure as demands are made elsewhere in the plumbing system. Symmons Temptrol® puts an end to “Shower Shock” and provides a safe, comfortable shower every time.



Symmons Temptrol® II
2000 Series
is available in
these finishes:



Polished
Chrome

Radiance®
Satin Nickel
(STN)

Radiance®
Polished Brass
(BRS)

Tub and Shower Systems



25-1

Temptrol® II (2000 Series)
Pressure-Balancing mixing valve with lever handle and adjustable stop screw to limit handle turn.
Clear-Flo showerhead with arm and flange.

15-2 Valve only



25-2

Temptrol® II (2000 Series)
Pressure-Balancing mixing valve with lever handle and adjustable stop screw to limit handle turn. Diverter tub spout, Clear-Flo showerhead, arm and flange.

15-2 Valve only



25-300-B30-V

Temptrol® II (2000 Series) Pressure-Balancing mixing valve with lever handle and adjustable stop screw to limit handle turn. Levertrol diverter with integral volume control.
Wall/hand shower with flexible metal hose, in-line vacuum breaker, wall connection and flange, 30" slide bar for hand shower mounting.



25-400-B30-V

Temptrol® II (2000 Series)
Pressure-Balancing mixing valve with lever handle and adjustable stop screw to limit handle turn. Diverter tub spout, wall/hand shower with flexible metal hose, in-line vacuum breaker, wall connection and flange, 30" slide bar for hand shower mounting.



25-500-B30-V

Temptrol® II (2000 Series) Pressure-Balancing mixing valve with lever handle and adjustable stop screw to limit handle turn. Lever diverter with integral volume control. Clear-Flo showerhead with arm and flange. Wall/hand shower with flexible metal hose, in-line vacuum breaker, wall connection and flange, 30" slide bar for hand shower mounting.



25-600-B30-V

Temptrol® II (2000 Series) Pressure-Balancing mixing valve with lever handle and adjustable stop screw to limit handle turn. Lever diverter with integral volume control. Tub spout. Clear-Flo showerhead with arm and flange. Wall/hand shower with flexible metal hose, in-line vacuum breaker, wall connection and flange, 30" slide bar for hand shower mounting.

Modifications: Suffix X: Integral service stops - allows water shutoff at valve for service • Suffix IPS: 1/2" female IPS connections • Suffix REV: Reverse coring, hot on right, cold on left, for back to back installations • Delete Suffix B30: 2 wall hooks in place of 30" bar • Suffix LR: Lever handle • Suffix LP: Loop handle