

SHOWER ACCESSORIES

S-2310



VS-111



Shower Accessories

□ S-2310

Polished chrome plated brass thumb operated volume control. 1/2" NPT connections.

□ VS-111

Chrome plated brass shower diverter. 1/2" NPSF inlet. 1/2" NPSM outlet and side port outlet.

□ VS-114

Chrome plated plastic/brass 2-way shower diverter. 1/2"-14 NPT Female threaded inlet and 1/2"-14 NPT Male bottom outlet. Swivel brass coupling nut. Handle turns 90° only. Operational diverter settings. Side port outlet. 1/2" - 14 NPSM male. No flow control inserted.

□ VS-115

Chrome plated brass supply ell with wall flange. 1/2" NPTF inlet. 1/2" NPSM outlet.

□ VS-117

Chrome plated brass in-line vacuum breaker. 1/2" NPSF inlet. 1/2" NPSM outlet. NOTE: Do not install VS-117 in concealed locations or where slight spillage under certain service conditions might cause water damage. Avoid continuous pressure applications (shut-off valve downstream of vacuum breaker).

□ VS-150

Chrome shower arm mount bracket to hold handheld shower. 1/2" -14 NPSM Threaded inlet and outlet. Easy seal and 2.5 GPM flow control inserted.

□ VS-152-6FT

Chrome 6' metal shower hose, 1/2"-14 NPSM female tangle free connectors.

□ VS-153-ADA

24" combination slide bar and grab bar, stainless steel and chrome. Meets the ANSI standard 250 lbs. pull-test for grab bars and with ADA lever handle for adjusting slide bar.

□ S-2590*

Polished chrome plated 10" pivoting extension shower arm. Raises or lowers the shower arm over a 20" range. Key included to set adjustment. 1/2" NPT connections.

OPTIONS

SUFFIX	DESCRIPTION
□ BN	Brushed nickel (VS-111, VS-114, VS-150, VS-153-ADA)
□ PB	Polished brass (VS-111, VS-114, VS-150, VS-153-ADA)

VS-115



VS-114



VS-150-PC



VS-153-ADA



VS-117



VS-152-6FT



S-2590*



This space for Architect/Engineer approval.



Management Systems Registered to ISO 9001

Versatile — T.M. Speakman Company
 © Copyright, Speakman Company, 2013