

IBOC® 300-9V BATTERY POWERED

1 STATION OUTDOOR



A highly reliable, battery-operated, valve-mounted controller designed to provide automatic valve operation in areas where a hardwire connection is impractical or for temporary operation of a valve when field wiring is cut or broken. Irritrol. Get more done.

SO EASY TO USE, YOUR ONLY CALLBACK WILL BE A THANK YOU.

KFY FFATIIRFS & RFNFFITS

REMOTELY PROGRAMMABLE WITH THE RCP8 PLUS (SOLD SEPARATELY) Allows convenient reprogramming

BATTERY-POWERED UNIT FEATURES LOW POWER CONSUMPTION For application without AC power

USES STANDARD 9V DC BATTERY Readily available (not included)

ADDED FEATURES

- Three start times per program
- Seven-day calendar or interval programming
- True odd/even programming with automatic 31st day skip
- Programmable "Rain Off" up to seven days
- Programmable address allows easy programming of multiple units in a single valve box
- Modular design allows for easy field programming
- Water-resistant construction provides reliable operation
- Retains program up to two minutes during battery replacement
- International icons with English captions
- Default program option allows for quick setup simply plug in battery and setup is complete
- LED lights verify program input and operation
- Fits all Irritrol irrigation valves with internal manual bleed

 requires VA12 adapter (included)
- Low-profile design fits in valve boxes
- Infrared programming overrides any manual program settings
- One-year battery life with typical operation
- Two-year controller warranty

OPERATING SPECIFICATIONS

- Station run times: 1 minute to 23 hours, 59 minutes
- Default program: 15 minutes of irrigation per day
- Four irrigation cycle options: once per day, twice per day, once per two days and once per seven days (when programmed manually)
- Pressure limit: 150 psi
- Operating temperature: 33° to 140°F
- Adapters available separately for other valve brands:
 - VA15 for Rain Bird[®] DV valves
 - VA20 for Nelson® valves
- BAT9VDC battery housing for IBOC300-9V (included with controllers and available separately; 9-volt alkaline battery not included)

DIMENSIONS

• **IBOC300-9V:** H: 3", W: 2 ¹/₂", D: 1 ¹/₂"



IBOC 300-9V