



4700 W. 160th St.  
Cleveland, OH 44135  
PH:800-321-9532  
FX:800-321-9535  
www.oatey.com

**TECHNICAL SPECIFICATION**

**RAIN COLLAR FOR  
NO-CALK ROOF FLASHING**



**Engineering Specification:** Oatey Rain Collar for No-Calk Roof Flashings can be used as a secondary seal for commercial and residential applications where a watertight seal for roof penetrations around the plumbing vent pipe is required.

**Job Reference**



- ◆ Non-fading sealing collar
- ◆ Not for hot-mopped or built-up roofs
- ◆ Do not use paint or petroleum based products on rubber collars
- ◆ Slides over existing roof flashing

✓	Product No.	Description	PACK	CARTON WEIGHT
	14122	1-1/4" - 1-1/2" Rain Collar for No-Calk Roof Flashing	36	2 lbs.
	14205	1-1/4" - 1-1/2" Rain Collar for No-Calk Roof Flashing	6	1 lbs.
	14135	2" Rain Collar for No-Calk Roof Flashing	24	2 lbs.
	14206	2" Rain Collar for No-Calk Roof Flashing	6	1 lbs.
	14193	3" Rain Collar for No-Calk Roof Flashing	24	3 lbs.
	14207	3" Rain Collar for No-Calk Roof Flashing	6	1 lbs.
	14203	4" Rain Collar for No-Calk Roof Flashing	12	5 lbs.
	14208	4" Rain Collar for No-Calk Roof Flashing	6	3 lbs.
	14136	1-1/2" - 3" Rain Collar for No-Calk Roof Flashing	24	3 lbs.
	14137	3" - 4" Rain Collar for No-Calk Roof Flashing	24	10 lbs.