




**Submitted Model No.:** Specific Features:



#### ▲ Designate Proper Finish Suffix





Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.

# DELTA

## **IB AND SHOWER** FAUCET TRIM

- Victorian® Collection
- Tub Only (T17155 Series)
- Shower Only (T17255 Series)
- Tub/Shower (T17455 Series)

#### **FEATURES:**

- Monitor® 17 Series pressure balanced bath mixing valve trim
- "-H2O" models include H<sub>2</sub>Okinetic<sup>®</sup> Technology shower-

### STANDARD SPECIFICATIONS:

- Maintains a balanced pressure of hot and cold water even when a valve is turned on or off elsewhere in the system.
- For use with MultiChoice<sup>®</sup> Universal rough valve body. (R10000 Series)
- Back-to-back installation capability.
- Solid brass forged body.
- Lever volume control handle; temperature adjustment dial.
- Field adjustable to limit handle rotation into hot water zone,
- Maximum dial rotation adjustable between 90° and 180°.
- All parts replaceable from the front of the valve.
- 2.5 gpm @ 80 PSI for multi setting showerhead and 2.0 gpm @ 80 PSI for models with -H2O suffix.
- Includes decorative trim ring (RP34359).
- Stem extension kit RP77992 can be ordered to allow for an additional 1 3/4" wall thickness.RP77992 ships with chrome escutcheon screws. For special finishes also order RP12630 escutcheon screws in desired finish.

#### WARRANTY

- Lifetime limited warranty on parts (other than electronic parts and batteries) and finishes:or, for commercial users, for 5 years from date of purchase.
- 5 year limited warranty on electronic parts (other than batteries); or, for commercial users, for 1 year from the date of purchase.

No warranty is provided on batteries.




#### **COMPLIES WITH:**

- ASME A112.18.1 / CSA B125.1
- ASSE 1016

Indicates compliance to ICC/ANSI A117.1 - Valve control only

EPA WaterSense®





55 E 111th Street, Indianapolis, Indiana 46280 350 South Edgeware Road, St. Thomas, ON N5P 4L1 © 2015 Masco Corporation of Indiana