



Not to be used in above-the-floor rough-in.

See price list for complete item numbers and available options.

When ordering, please specify complete item number and any applicable option codes.



For More Information Contact:
WATCO Manufacturing Company
 1220 South Powell Road
 Independence, MO 64057-2724
 Ph. 816-796-3900 • FAX 816-796-0875
www.watcomfg.com

Tubular Brass

TURNSTYLE® 501-TS

TURNSTYLE® 502-TS

For most tubs 14" - 16" high

TURNSTYLE® 551-TS

TURNSTYLE® 552-TS

For most tubs up to 24" high

**Sturdy 1.5" 17g and 20g Tubular Brass
 Slip-Joint Assembly**

SPECIFICATIONS

FEATURES:

- Will fit most tub angles
- The look of a cable drive without the potential for behind-the-wall repair.
- Strainer body cover catches hair.
- Metal handle and strainer body.
- No stopper in drain ell, therefore...
 - no stopper adjustments required
 - theft resistant
 - no stubbing-the-toe injuries
- Retainer plate for overflow elbow

APPROVALS:

- Manufactured in compliance with ASME A112.18.2-2005/CSA B125.2-2005; and TIL MSE-051.

PATENTS:

- See <http://watcomfg.com/Watco/patents/> for Details

OPERATION:

- Turn overflow plate clockwise to close drain and counter-clockwise to open drain.

THREAD SIZE (Strainer Body and Drain Elbow):

- 1½" – 11½ NPSM (Coarse Thread)
- 1.865" Major Diameter (outside thread diameter)
- 11.5 threads per inch

PIPING:

- 17g: 501 models
- 20g: 502 models

FINISHES:

- CP - Chrome Plated
- BN - Brushed Nickel
- BO - Bone
- BS - Biscuit
- BZ - Oil-Rubbed Bronze
- CB - Chrome Brushed
- NP - Nickel Polished
- PB - Polished Brass
- WH - White
- WI - Wrought Iron