


# DuraTech® 5"-8"

## Chimney Pipe



**5" - 8" Diameters** - Designed for appliances that are tested and listed for use with a 2100° F HT chimney system, such as wood stoves, fireplaces, furnaces, boilers, ranges, water heaters, or other appliances fueled by wood, oil, coal, or gas. Available in stainless steel (SS) or in a galvalume (GA) outer casing and stainless steel inner wall with twist-lock connections.

DuraTech 24", 36", 48", and 60" chimney pipe is available with additional protective carton filler for shipping. Available items have stock numbers with (CF).

| SIZE      | 5"       | 6"       | 7"       | 8"       |
|-----------|----------|----------|----------|----------|
| A         | 5"       | 6"       | 7"       | 8"       |
| B         | 7"       | 8"       | 9"       | 10"      |
| LENGTH    |          |          |          |          |
| 6" GA     | --       | 9402GA   | 9502GA   | 9602GA   |
| 6" BLACK  | 9302B    | 9402B    | 9502B    | 9602B    |
| 6" SS     | 9302     | 9402     | 9502     | 9602     |
| 9" GA     | --       | 9408GA   | 9508GA   | 9608GA   |
| 9" BLACK  | 9308B    | 9408B    | 9508B    | 9608B    |
| 9" SS     | 9308     | 9408     | 9508     | 9608     |
| 12" GA    | --       | 9403GA   | 9503GA   | 9603GA   |
| 12" BLACK | 9303B    | 9403B    | 9503B    | 9603B    |
| 12" SS    | 9303     | 9403     | 9503     | 9603     |
| 18" GA    | --       | 9404GA   | 9504GA   | 9604GA   |
| 18" SS    | 9304     | 9404     | 9504     | 9604     |
| 24" GA    | --       | 9405GA   | 9505GA   | 9605GA   |
| 24" GA    | 9305GACF | 9405GACF | 9505GACF | 9605GACF |
| 24" SS    | 9305     | 9405     | 9505     | 9605     |
| 24" SS    | 9305CF   | 9405CF   | 9505CF   | 9605CF   |
| 36" GA    | --       | 9406GA   | 9506GA   | 9606GA   |
| 36" GA    | --       | 9406GACF | 9506GACF | 9606GACF |
| 36" SS    | 9306     | 9406     | 9506     | 9606     |
| 36" SS    | 9306CF   | 9406CF   | 9506CF   | 9606CF   |
| 48" GA    | --       | 9407GA   | 9507GA   | 9607GA   |
| 48" GA    | --       | 9407GACF | 9507GACF | 9607GACF |
| 48" SS    | 9307     | 9407     | 9507     | 9607     |
| 48" SS    | 9307CF   | 9407CF   | 9507CF   | 9607CF   |
| 60" GA    | --       | 9409GACF | 9509GACF | 9609GACF |
| 60" SS    | 9309CF   | 9409CF   | 9509CF   | 9609CF   |

To calculate installed length of 5", 6", 7", or 8" DuraTech Chimney, subtract 1 ¼" from each joint overlap of chimney pipe. Allow a minimum of 2" air space to combustibles when installing DuraTech Chimney.