


### 30° Elbow




Use for offsets around obstructions such as rafters, ridgepoles, or joists. May have one pair of elbows if needed. Offsets greater than 30° are not permitted in accordance to UL 103 standards. Large diameters are restricted to one pair of elbows.

Available in galvalume (GA) and stainless steel (SS) outer wall and stainless steel inner wall. Fasten with screws.

| SIZE       | 10"     | 12"     | 14"     | 16"     | 18"     | 20"     | 22"     | 24"     |
|------------|---------|---------|---------|---------|---------|---------|---------|---------|
| A          | 10"     | 12"     | 14"     | 16"     | 18"     | 20"     | 22"     | 24"     |
| B          | 12"     | 14"     | 16"     | 18"     | 20"     | 22"     | 24"     | 26"     |
| C          | 5 7/8"  | 6 1/8"  | 6 3/8"  | 6 5/8"  | 9"      | 9"      | 9"      | 9"      |
| D          | 6 5/8"  | 6 7/8"  | 7 1/8"  | 7 3/8"  | 9"      | 9"      | 9"      | 9"      |
| GA STOCK # | 99166   | 99266   | 99366   | 99466   | 99566   | 99666   | 99766   | 99866   |
| SS STOCK # | 99166SS | 99266SS | 99366SS | 99466SS | 99566SS | 99666SS | 99766SS | 99866SS |


### Elbow Strap



Use to prevent excessive weight on the elbows by supporting the weight of the chimney. Required to be installed between two elbows in offset installations. Multiple elbow straps may be required for offset installations. Refer to installation instructions.

| SIZE    | 10"   | 12"   | 14"   | 16"   | 18"   | 20"   | 22"   | 24"   |
|---------|-------|-------|-------|-------|-------|-------|-------|-------|
| A       | 12"   | 14"   | 16"   | 18"   | 20"   | 22"   | 24"   | 26"   |
| B       | 30"   | 30"   | 30"   | 30"   | 36"   | 36"   | 36"   | 36"   |
| STOCK # | 99160 | 99260 | 99360 | 99460 | 99560 | 99660 | 99760 | 99860 |

### Round Ceiling Support Box



Supports chimney pipe and provides a positive connection between support box and chimney. Supports up to 40' of DuraTech Chimney. Trim collars are sold separately. (For 10" use DuraBlack Slip Connector to attach DuraBlack to the support box. See DVL/DuraBlack section).

| SIZE    | 10"      | 12"      | 14"      | 16"      |
|---------|----------|----------|----------|----------|
| A       | 10 5/16" | 12 5/16" | 14 5/16" | 16 5/16" |
| B       | 14"      | 16"      | 18"      | 20"      |
| C       | 16"      | 18"      | 20"      | 22"      |
| STOCK # | 99145    | 99245    | 99345    | 99445    |