This unit offers anti-siphon protection.

The Woodford Model 25 drains as handle is shut off <u>even</u> <u>if hose is attached</u>. This faucet is designed for outside residential water service applications and intended for irrigation purposes.

SPECIFICATIONS:

MODEL 25 - Approved under ASSE Standard 1019-B and listed by IAPMO®. MeetsGovernment Specification WW-541b Type 205.

Vacuum Breaker - Anti-Siphon

NIDEL® model 34HA with 3/4" male hose thread. Approved under ASSE Standard 1011. Canadian Standards Association and listed by IAPMO®.

FEATURES:

EXTERIOR FINISH - Brass

VALVE - Molded nitrile suitable for hot water.

NOZZLE - 3/4" male hose thread.

NO LEAD SOLDER - All solder joints.

PLUNGER - Hemispherical cushion type.

STEM SCREW - DELRIN®

HEAD NUT - Brass

HANDLE - Metal. (Optional Tee Key)

INLETS - As shown.

MAX PRESSURE - 125 p.s.i.

MAX TEMPERATURE - 120° F

NOTICE - To close and drain, turn handle clockwise until seated and water drains out of the drain hole or faucet may freeze and burst. Vacuum Breaker replacement is recommended every 3-5 years.

Rough-In Dimensions OVERALL LENGTH WALL INIET THICKNESS ALIGNING MARK

Wall Thickness (inches)

| 4 | 6 | 8 | 10 | 12 | 14 | 16 | 18 | 20 | 22 | 24 |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| 2.0 | 2.1 | 2.2 | 2.3 | 2.4 | 2.5 | 2.7 | 2.9 | 3.1 | 3.3 | 3.5 |

Shipping Wt. (lbs)

Approx. Shipping Weight Each

*Overall Length Dimension: Add wall thickness and inlet option length shown in chart at right.

Patent informaion available at:

http://www.woodfordmfg.com/Woodford/patents/ For Installation/Troubleshooting Instructions go to: www.woodfordmfg.com or call 1-800-621-6032


Anti-Siphon

Automatic Draining Freezeless Wall Faucet Model 25


WOODFORD




Inlet Descriptions




C Inlet COMBINATION Copper Sweat Fitting 1/2" K, L or M Inside 3/4" M Only Outside




CP Inlet COMBINATION 1/2" Male Pipe Thread 1/2" Female Sweat



CP3 Inlet COMBINATION 3/4" Male Pipe Thread 3/4" Female Sweat



P Inlet COMBINATION 1/2" Female Pipe Thread 3/4" Male Pipe Thread



PX Inlet 1/2" PEX Tube Fitting PX3 INLET 3/4" PEX Tube Fitting

When ordering, specify model, inlet and wall thickness.

©2019 WOODFORD Mfg. Rev. 04/19 Form No. 25.108