



M922880-0020A & M922881-0020A Shown

FEATURES & BENIFITS:

- **Less Water:** 1.5 gpm maximum flow rate delivers 32% water savings (when compared to standard 2.2 gpm).
- **Superior Performance:** Pressure compensation provides a constant flow throughout the entire pressure range.
- **Lead Free:** Complies with CA AB1953 and VT S152

MODEL NUMBER:

- ☐ **1.5 gpm / 5.7 L/min Pressure Compensating Aerators**
 - M922881-0020A: 15/16" Male
 - M922880-0020A: 55/64" Female
- ☐ **1.5 gpm / 5.7 L/min Pressure Compensating Vandal-Resistant Aerators (with Key) - Used in V15 modifications**
 - M922887-0020A: 15/16" Male
 - M922888-0020A: 55/64" Female
- ☐ **1.5 gpm / 5.7 L/min Pressure Compensating Non-Aerated Laminar Flow Outlet - Used in L15 modifications**
 - M922883-0020A: 15/16" Male
 - M922884-0020A: 55/64" Female
- ☐ **1.5 gpm / 5.7 L/min Pressure Compensating Vandal-Resistant Non-Aerated Laminar Flow Outlet (with Key) - Used in LV15 modifications**
 - M922885-0020A: 15/16" Male
 - M922886-0020A: 55/64" Female

