





Sloan Prison 603 S.S. — Rev. 0a (11/10) Copyright © 2010 SLOAN VALVE COMPANY

Sloan® Prison Model Flushometer



Description

Concealed Water Closet Flushometer, for Stainless Steel Combination Fixtures. For use with: Acorn® • Bradley® • Metcraft® (Series 3000) • Willoughby® and similar fixtures.

Flush Cycle

- ☐ Model 603 Water Saver (3.5 gpf/13.2 Lpf)
- ☐ Model 603-1.6 Low Consumption (1.6 gpf/6.0 Lpf)

Specification:

Quiet, Concealed, Diaphragm Type, Rough Brass Closet Flushometer for either left or right hand supply with the following features:

- High Chloramine Resistant PERMEX™ Synthetic Rubber Diaphragm with Linear Filtered Bypass and Vortex Cleansing Action™
- Metal Direct Acting, Non-Hold-Open Push Button with a Triple Seal Handle Packing
- 1" I.P.S. Wheel Handle Bak-Chek® Angle Stop
- Adjustable Tailpiece
- Vacuum Breaker
- Elbow Flush Connection and Coupling for 1-1/2" NPT Back Inlet (for connection in the pipe chase flush connection through the wall not provided by Sloan)
- Exposed parts Chrome Plated
- High Copper, Low Zinc Brass Castings for Dezincification Resistance
- Low Consumption Flush Accuracy
- Handle Packing, Stop Seat and Vacuum Breaker molded from PERMEX™ Rubber Compound for Chloramine Resistance
- 100% of the energy used in manufacturing is offset with Renewable Energy Sources – Wind Energy

Valve Body, Cover, Tailpiece and Control Stop shall be in conformance with ASTM Alloy Classification for Semi-Red Brass. Valve shall be in compliance to the applicable sections of ASSE 1037.

L Dimension

Specify the "L" Dimension for the proper length of the Push Button Assembly. The "L" Dimension is equal to the Wall Thickness (to the nearest whole inch) plus 434".

Variations □ AFD

	(Anti-Flood Device NOT provided by Sloan) *Not required for use with	
	Bradley Flood Buster®	
□ DFB	Dual Filtered Fixed Bypass Diaphragm	
□ ES	Solenoid Operated (specify 24 VAC or 120 VAC)	
□ ESM	Solenoid Operated with Modular Plug for use with Sloan PWT Systems (24)	

Shorter Vacuum Breaker — for use with Anti-Flood Device

VAC only)
See Accessories Section of the Sloan catalog for details on these and other Flushometer variations.









This space for Architect/Engineer approval		
Job Name	Date	
Model Specified	Quantity	
Variations Specified		
Customer/Wholesaler		
Contractor		
Architect		

The information contained in this document is subject to change without notice.



Made in the U.S.A.

SLOAN VALVE COMPANY • 10500 SEYMOUR AVE. • FRANKLIN PARK, IL. 60131
Ph: 1-800-9-VALVE-9 or 1-847-671-4300 • Fax: 1-800-447-8329 or 1-847-671-4380
www.sloanyalve.com