



Can be installed
left high and right low,
OR right high and left low

BARRIER-FREE UNIVERSAL SPLIT-LEVEL VERSACOOLER® II

P8ACSL, PACSL

Suggested Specification

Model P8ACSL shall deliver 8.0 gph of 50° F degree water at 90° F ambient and 80° F inlet water. Model PACSL is a non-refrigerated drinking fountain and delivers ambient water. Models P8ACSL and PACSL shall include front and side push pads to activate the flow of water. Basin shall be designed to eliminate splashing and standing water. Bubbler shall have flexible guard and operate between 20 and 120 PSI. Cabinet finish shall be Sandstone powder coated paint on galvanized steel or brushed stainless steel. Cooling system shall use R-134a refrigerant. Shall comply with ANSI A117.1 and ADA. Shall be listed by Underwriters' Laboratories to U.S. and Canadian standards. Shall comply with ANSI/NSF 61.

Models

P8ACSL delivers 8.0 gallons of chilled drinking water per hour

PACSL is a non-refrigerated fountain.

Standard Features

- > Built-in 100 micron strainer stops particles before they enter the waterway
- > Waterways are Lead-Free In Materials & Construction
- > Stainless Steel Top
- > Flexible, one piece Bubbler Guard
- > Heavy Duty Galvanized Steel Frame
- > High Efficiency Cooling Tank and Coil
- > Refrigerant R-134a
- > Four Push Pad Mechanical Activation
- > External Stream Height Adjustment

Finishes

- > Standard Cabinet Finish: Sandstone powder coated paint on galvanized steel
- > Optional finishes (at additional cost): Stainless Steel, Regency Bronze, and optional powder coated finishes

Installation

- > Prior to roughing consult with local, state, and federal codes for proper mounting height.
- > Shipped with complete instructions and wall mounting bracket.
- > Removable side and front panels provide easy access for installation

Options

- Glass Fillers (Factory Installed)
- Push Handle (029603-004)
- Push Back (029603-005)
- Push Down (029603-006)
- Apron for Upper Unit
- Once Piece Chrome Plated Brass Bubbler (036700-001)

Powder Coated Finish Warranty (Continental limits of the United States and Canada): Three years on the powder coat finish provided that the water cooler has not been subjected to abuse, misuse, or alteration.

Limited 5-Year Warranty (Continental limits of the United States and Canada): Five years on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each water cooler; sample available upon request.

Export Warranty: One year on the sealed refrigeration system and most component parts. Detailed warranty certificate enclosed with each drinking fountain; sample copy available upon request.

Models covered by this specification comply with all known Plumbing Codes. Listed by Underwriters Laboratories to U.S. and Canadian standards.

Components in this fountain are lead free as defined by the Safe Drinking Water Act Amendments of 1986, and the Lead Contamination Control Act of 1988.

ADA Compliant when properly installed

These units comply with A.R.I. Standard 1010



Oasis International Product
Certified by NSF to
NSF/ANSI Standard 61, G

Model	50° F Drinking Water 90° F Ambient Air Temp*			Hot'N Cold™ Model	115 Volts, 60 HZ			Glass Filler Acc. Option	Cabinet Color Finish	Net Wt. Approx.
	Rated Capacity GPH	Base Rate GPH	Pre-Cooler		Compr. HP	Full Load Amps	Rated Watts			
P8AC**	8.0	8.0	No	No	1/4	4.4	500	Yes	Yes	69 Lbs.
PAC	Fountain Only							Yes	Yes	25 Lbs.

*Industry Standard Rating Condition 80° F inlet water temperature.

**Special export models available, operable on 220-240 volts, 50/60 HZ.

Specifications subject to change without notice

OASIS® BARRIER-FREE SPLIT-LEVEL Versacooler® II MODELS PACSL, P8ACSL, PGACSL, PG8ACSL, P8ACSL

