

This unit offers backflow and bursting protection.

The Woodford Model C22 chrome plated commercial wall faucet is designed for irrigation purposes to provide year-round hot and cold water service regardless of outside temperature. Separate hot and cold inlet tubes and operating handles allow for manually operated water temperature control. Use on any commercial structure where intermittent hot and cold water service is required.

**Freezeless
Hot & Cold
Wall Faucet
Model C22/B22**



Available in two models:

- Model C22 - Chrome Plated
- Model B22 - Chrome Plated

Includes flush mounted chrome plated brass box

- B22 available in rough brass: B22-BR

SPECIFICATIONS:

MODEL 50HA BACKFLOW PREVENTER -

Patent Pending

- ASSE 1052 Approved
- Listed by IAPMO
- Field Testable
- Two Independent Check Valves
- Drains automatically when hose is removed
- No spray back



Nozzle - 3/4" male hose thread

Valve Operating Threads - Full circle threads on valve body and retainer

No Lead Solder - All solder joints

Seat Washer - Standard "O" size

Max. Pressure - 125 p.s.i.

Max. Water Temperature - 120° F

FEATURES:

- An internal resetting pressure relief valve prevents the faucet casing tube from bursting in freezing conditions even if a hose is unintentionally left on.
- 5" center to center handle spacing.
- Faucet drains automatically when hose is removed.
- Permanent stainless steel seat will not wire draw.
- EPDM packing to prevent leaking.
- Loose Tee Key - optional

OPTIONAL: An RK-PT Conversion Kit is available for the C22 at additional cost to convert the hot side handle to a Push to Turn. This will reduce the potential to unintentionally turn on the hot water.

U.S. Patents: Manufactured under one or more of the following patents: 3,208,715; 3,278,201; 5,590,679; 5,632,303; 6,142,172; 6,206,039B1; 6,532,986 and patents pending

Model C22 Shipping Weight

Wall Thickness (inches)

CC	4	6	8	10	12	14	16	18	20	22	24
2.8	3.1	3.3	3.5	3.8	3.9	4.2	4.6	4.8	5.0	5.2	5.4

Shipping Wt. Ea. (lbs)
Add 14.7 Lbs. for B22 (box) models.




Model C22




Model B22


INLET OPTIONS




C INLET COMBINATION
Copper Sweat Fitting
1/2" K,L or M Inside
3/4" M Only Outside




CP INLET COMBINATION
1/2" Male Pipe Thread
1/2" Female Sweat




CP3 INLET COMBINATION
3/4" Male Pipe Thread
3/4" Female Sweat



P INLET COMBINATION
1/2" Female Pipe Thread
3/4" Male Pipe Thread



PX INLET
1/2" PEX Tube Fitting
PX3 INLET
3/4" PEX Tube Fitting



C1 INLET
1/2" Female Sweat Fitting
22 Close Coupled ONLY

**For Installation / Troubleshooting Instructions go to
www.woodfordmfg.com or call 1-800-621-6032**

When ordering, specify model, inlet and wall thickness