



Backflow Protected Wall Faucets

Model 26/B26/Y26

The Model 26 and B26 are field testable, backflow protected wall faucets intended for irrigation purposes in mild climate areas. The Model B26 is enclosed in a wall mounted box. Both models are designed to blend with modern architecture for installation on or in homes, service stations, churches, motels, drive-in restaurants, etc. The Model Y26 is designed to be used on a stand pipe in the lawn and garden, etc.

SPECIFICATIONS:

MODEL 50HF BACKFLOW PREVENTER -

Patent Pending

- ASSE 1052 Approved
- Listed by IAPMO
- Field Testable
- Two Independent Check Valves
- Drains automatically when hose is removed
- No spray back

FEATURES:

EPDM PACKING: Prevents leaking.

PACKING NUT: Adjustable brass nut with deep stem guard.

VALVE SEAT: Standard "O" size washer.

HANDLES: Furnished with polycarbonate wheel handle and loose tee key. **Optional:** Metal wheel handle.

INLETS: Model 26 as shown below.
Model B26: 26P- 1/2" or 26P 3/4" only.
Model Y26: 3/4" FPT.

MAX PRESSURE: 125 p.s.i.

MAX TEMPERATURE: 120° F

SHIPPING WEIGHT: (per unit)

MODEL 26 & Y26: 1.2 lbs

MODEL B26: 14.6 lbs (brass or chrome box)
6.5 lbs (aluminum box)



MODEL 26

Exterior Finish:

Standard - Chrome

Optional- Rough Brass (BR) or Polished Chrome (PC)



MODEL B26

Exterior Finish:

Standard - Chrome

Optional- Rough Brass (BR) or Polished Brass (PB)

Other Options: Anodized Aluminum Box and Door



MODEL Y26

Exterior Finish:

Standard - Chrome

Optional- Rough Brass (BR) or Polished Chrome (PC)

Inlet Descriptions


MODEL 26/B26

P-1/2" Inlet

1/2" FPT

P-3/4" Inlet

3/4" FPT




MODEL 26 ONLY

CP Inlet

COMBINATION

1/2" COPPER TUBE

1/2" MPT




MODEL 26 ONLY

C Inlet

COMBINATION

1/2" COPPER TUBE

3/4" COPPER TUBE



**For Installation / Troubleshooting Instructions go to
www.woodfordmfg.com or call 1-800-621-6032**