



Mirror cabinet	Dimension	Weight	Order number
cIAPMO®ELECTRICAL, 2 mirror doors, 2 glass shelves (clear glass), back panel inside mirror glass, GFCI outlets are not supplied by the manufacturer (GFCI outlets can be added to the cabinet by a certified electrician on the job site), 1 sensor switcl bottom right, Mirror cabinets require a GFCI 110 V 60 Hz power source. Flat plug will be supplied with the mirror cabinet, LED dimming function, LED (life span > 30,000 hours), LED module permanently enclosed, LED module 3500 Kelvin light color, 46 W	h		
Colors			
M00			
Variant			
	39 3/8" x 6 1/8" lr	nch	LC755200000
Infobox			
# LC 7551 and LC 7552 are available from stock, Stocked item of between sensor and reflecting surfaces = minimum 3"	does not include add	itional modules, Distance	
Additional modules cIAPMO®ELECTRICAL, LED downlight for washbasin area 3500 kelvin light color, 3 W, LED dimming function, LED (life span > 30,000 hours), LED module permanently enclosed			UV9954

All drawings contain the necessary measurements which are subject to standard tolerances. They are stated in inch & mm and are non-binding. Exact measurements, in particular for customized installation scenarios, can only be taken from the finished ceramic piece.