



Satisfy Professional's Needs

Hypoid Saw
5477NB 185mm (7-1/4")

TOUGH & MUSCULAR



Max. bevel capacity 51.5 degrees.



**Powerful
15AMP
Motor**

Hex wrench holder



Ergonomic top and rear handles positioned, angled, and contoured for best fitting and easy handling

Handle can be replaced without replacing Motor housing.

Non-skid elastomer grip provides more control and comfort.

Easy-to-read cutting depth scale

with the two most common depths, 19mm (3/4") and 13mm (1/2"), printed in large type.



Safety Cover

Designed to move smoothly.

Scale with easy-to-read calibrations



Easy to replace the Base because the Base is attached by screws.

Positive stopper for 45° bevel cat

Notches to align with cutting line for bevel angle 0 degrees and 45 degrees

Practical Blade Fastening Bolt

Can be tightened/ loosened with either socket wrench or hex wrench.




Max. cutting depth

60mm

(2-3/8")

Greater than competing models available in the market



Max. bevel capacity

51.5degrees



Positive stop

45degrees

Bevel adjustment with positive stop at 45 degrees.



Hypoid Saw

Double insulation



5477NB 185mm (7-1/4")

153

Capacity	at 0 degrees : 60mm (2-3/8") at 45 degrees : 44mm (1-3/4") at 50 degrees : 40mm (1-9/16")
Blade diameter	185mm (7-1/4")
No load speed (rpm)	4,500
Dimensions(L x W x H)	442 x 183 x 254mm(17-3/8" x 7-1/4" x 10")
Net weight	6.3kg (13.9lbs)

Standard Equipment T.C.T Saw Blade, Hex Wrench

Optional Accessories

Guide rule
Part No. 165153-3

Hook ass'y
Part No. 125346-4



Items of standard equipment and specifications may differ by country or area.

Makita Corporation

3-11-8 Sumiyoshi-cho, Anjo, Aichi, 446-8502 Japan

PRINTED IN JAPAN Z23418-2 AI-BB