



Contemporary

**SPECIFICATIONS – MicroTouch Control**

|                     |                            |
|---------------------|----------------------------|
| Construction.....   | 6061 Billet Aluminum       |
| Display.....        | 16 LED Temperature Display |
| Interface.....      | 3 Capacitive Touch Buttons |
| Communication.....  | ThermaSol CAN Bus          |
| Supply Voltage..... | 5V DC                      |

**Basic Functions:**

- Recall last steam settings
- Turn steam system on or off
- Set desired steam shower temperature
- Operate PowerFlush™ cleaning system
- Diagnostic LEDs, display troubleshooting errors codes
- Patent Pending Infrared temperature sensing
- Smooth operation with capacitive touch technology (CTT)

**Installation Notes:**

The control should be installed 60” inches from the floor of the shower, inside the shower only, and away from the steam head.

**Finish Chart:**

Select desired finish and replace XXX with code.

|                       |                         |
|-----------------------|-------------------------|
| PC = Polished Chrome  | PN = Polished Nickel    |
| SC = Satin Chrome     | SN = Satin Nickel       |
| PB = Polished Brass   | BN = Black Nickel       |
| SB = Satin Brass      | AN = Antique Nickel     |
| AB = Antique Brass    | PG = Polished Gold      |
| COP = Polished Copper | ORB = Oil Rubbed Bronze |
| ACOP = Antique Copper | WHT = White             |

**Product Specification:**

The user interface control shall be 2.9” Dia x .63” in dimension. The Control shall be made from billet aluminum and includes the ability to operate and control: Smart Steam and PowerFlush™ System, using 100% networked digital technology.

**Shipping Information:**

Weight..... 4 lbs.  
 Length.....12 in.  
 Width.....12 in.  
 Height.....6 in.

**Styling Information:**

The control is shown in Contemporary



Contemporary Edge

For any further assistance please contact ThermaSol at 800.776.0711 or [sales@thermasol.com](mailto:sales@thermasol.com)

