



Contemporary

SPECIFICATIONS – MicroTouch Control

| | |
|---------------------|----------------------------|
| Construction..... | 6061 Billet Aluminum |
| Display..... | 16 LED Temperature Display |
| Interface..... | 3 Capacitive Touch Buttons |
| Communication..... | ThermaSol CAN Bus |
| Supply Voltage..... | 5V DC |

Basic Functions:

- Recall last steam settings
- Turn steam system on or off
- Set desired steam shower temperature
- Operate PowerFlush™ cleaning system
- Diagnostic LEDs, display troubleshooting errors codes
- Patent Pending Infrared temperature sensing
- Smooth operation with capacitive touch technology (CTT)

Installation Notes:

The control should be installed 60” inches from the floor of the shower, inside the shower only, and away from the steam head.

Finish Chart:

Select desired finish and replace XXX with code.

| | |
|-----------------------|-------------------------|
| PC = Polished Chrome | PN = Polished Nickel |
| SC = Satin Chrome | SN = Satin Nickel |
| PB = Polished Brass | BN = Black Nickel |
| SB = Satin Brass | AN = Antique Nickel |
| AB = Antique Brass | PG = Polished Gold |
| COP = Polished Copper | ORB = Oil Rubbed Bronze |
| ACOP = Antique Copper | WHT = White |

Product Specification:

The user interface control shall be 2.9” Dia x .63” in dimension. The Control shall be made from billet aluminum and includes the ability to operate and control: Smart Steam and PowerFlush™ System, using 100% networked digital technology.

Shipping Information:

Weight..... 4 lbs.
 Length.....12 in.
 Width.....12 in.
 Height.....6 in.

Styling Information:

The control is shown in Contemporary



Contemporary Edge

For any further assistance please contact
 ThermaSol at 800.776.0711 or
sales@thermasol.com

