

| Maintenance service card | | | |
|--|--|-----------------|--|
| Item number | | | |
| Serial number | | Purchasing date | |
| TE Lumber | | | |
| <p>Maintenance Regulations</p> <p>1. From the date of purchasing this series products, the length of warranty is one year. However, the following situation is beyond maintenance range:A. Product is damaged for inappropriate usage, maintenance, keeping by customer.B. For the damage of product is not installed or maintenance by EAGO distributor or appointed installation organization of services. (Concluding the damage is caused by customer's installation, taking apart, transportation and maintenance.) C. Without three guarantees of quality warranty, effective invoice or proof of purchase. D. Effective evidential documents and maintenance evidential documents can not be altered.E. The damaged is caused by force majeure or natural disaster.</p> <p>2. If the damage is caused by quality of product, repair and parts replacement will be provided for free.</p> <p>3. It is not damaged by the quality of product, or product exceeds protection period, cost expenses of repair and parts should be paid.</p> | | | |

The first page is kept for the customer.

| Maintenance service card | |
|--------------------------|--|
| Item number | |
| Serial number | |
| Customer name | |
| TE Lumber | |
| Address | |
| Agent shop | |
| TE Lumber | |
| Purchasing date | |

The second page is sent back to eago head office.

Safety Information

- 1.Please read carefully and follow all instructions when operating.
- 2.Qualified earth leakage circuit-breaker must be installed and tested with trial jump to certify the device is qualified and safety before using the product.
- 3.To avoid electric shock, the replacing of the wire must be done by the electrical engineer or the retailer. Customer could not replace just by yourself. The wire for CT,TS series shall be:3*1.5 mm²; The wire for TS-1,CL,CW , CW1 and S series shall be 3*1.0 mm².
- 4.Ground wire of massage water pump and air pump must be connected to ground well, the minimum size copper wire of ground wire must not be less than 1.5mm².
- 5.It is forbid to remodel, add or take part products.
- 6.Please don't use this product after alcohol or drugs.
- 7.The children shall be closely supervised by parents to use product.
- 8.All the electrical spare parts except the remote control must be put suitable and stable to avoid slip into the tub.
- 9.Warning:the mixed water temperature shall never exceed 60 degree centigrade.
- 10.Don't use sulphuric acid, hydrochloric acid, lye and other mixed strong corrosive chemical liquid to clean product.
- 11.The water pump would be very hot when running.Please don't touch the surface of the machine to avoid scald.
- 12.The water level must be higher than the jet before turning on the product.
- 13.Please don't drop anything in or insert in water pump and the opening hole of machine.
- 14.Warning: Avoid electrical shock, the GFCI/RCD (Earth Leakage Circuit Breaker) must be installed to ground socket for protection.
- 15.Warning: Avoid electrical shock, not allow to useing extended power wire.The socket position should be suitable.

Maintenance instruction

- 1.Clean the acrylic surface :**
 Clean acrylic surface with cotton flannel or sponge and water in daily life. If there is scratch on the surface, please use No. 1500 water abrasive cloth polishing slightly to clear away scratches, and then polish with toothpaste, cotton flannel. Please don't use strong caustic chemical liquid, such as sulphuric acid, hydrochloric acid, lye during maintenance.
- 2.Plated item maintenance:**
 Clean the surface of plated item with cotton flannel, please don't use coarse cloth.
- 3.Suction net cleaning:**
 Turn the screw out and take the suction net out to clear dirt, to keep the water going through smoothly. Don't use strong causticity chemical liquid to clean the product, such as sulphuric, hydrochloric acid, lye and so on.

