

Submitted Model No.:

Specific Features:



DELT

see what Delta can do

BATHROOM FAUCETS

Modern Series

Single Handle Deck Mount

STANDARD SPECIFICATIONS:

- Max. flow rate 1.2 gpm @ 60 psi, 4.5 L/min @ 414 kPa
- GPM models provide 1.0 qpm @ 60 psi, 3.8 L/min @ 414 kPa
- HGM models provide 0.5 gpm @ 60 psi, 1.9 L/min @ 414 kPa
- One or three hole mount (Escutcheon optional, not included) • Control mechanism is the ceramic disc cartridge with
- temperature limiter
- Red/blue indicator markings
- · Control handle shall return to neutral position when valve is turned off
- Solid brass body
- Lift rod hole plug included
- 1/4" threaded stud mounting
- Models have 50/50 pop-up type fitting with plated flange and stopper
- Models with suffix "MPU" have metal drain with pop-up
- type fitting with plated flange and stopper
- 559LF-BLGPM-PP has a metal drain with pop-up type fitting with plated flange and stopper

WARRANTY

- · Parts and Finish Lifetime limited warranty; or for commercial purchasers, 10 years for multi-family residential (apartments and condominiums) and 5 years for all other commercial uses, in each case from the date of purchase.
- Electronic Parts and Batteries (if applicable) 5 years from the date of purchase; or for commercial purchasers, 1 year from the date of purchase. No warranty is provided on batteries.



COMPLIES WITH:

- ASME A112.18.1 / CSA B125.1
- ASME A112.18.2 / CSA B125.2
- Indicates compliance to
- ICC/ANSI A117.1- Valve control only
 EPA WaterSense[®] Applies to 559LF-PP,
- 559LF-GPM-PP, 559LF-BLGPM-PP and 559LF-MPU-PP only

▲ Designate Proper Finish Suffix

Delta reserves the right (1) to make changes in specifications and materials, and (2) to change or discontinue models, both without notice or obligation. Dimensions are for reference only. See current full-line price book or www.deltafaucet.com for finish options and product availability.

Delta Faucet Company

55 E. 111th Street, Indianapolis, IN 46280 350 South Edgeware Road, St. Thomas, ON N5P 4L1 © 2020 Delta Faucet Company