

STEAM GENERATOR

- 1 year in-home warranty
- 2 year at the factory, after in-home
- · Superior incoloy heating elements low watt density
- · Constant steam at a constant rate
- Stainless steel construction
- Can be plumbed 50 ft. from the shower
- 50 ft. control cable included
- Sizing is easy L x W x H = Steam Room Cubic Feet



MODEL	INPUT VOLTAGE	KW RATING	AMPS	WIRE	BREAKER	PHASE	MAX. ROOM SIZE
LS-130	208-240VAC	8.0	37	8	40	1	175 CU.FT.
LS-375	208-240VAC	11	55	6	60	1	395 CU.FT.

Weight: 25 lbs.

Water Inlet: 3/8" NPT

Steam Outlet: 1/2" NPT Safety Valve: 3/4" NPT

Installation Notes

Generator is factory sized

- L x W x H = Steam Room Cubic Feet
- Always round up when calculating the total cubic feet.
- Then choose the appropriate generator.
- Ceiling height should not exceed 8 ft.

Please check date of your Net Price sheet for current pricing

CONTROL KITS

Your choice of either control kit to complete your package



4"w x 2-1/4"h x 3/4"d



1-1/2" x 1-1/4" x1 1/2"

CONTROL KIT STTC-OSS-XX*

Available in PC, PN, SN, ORB

Control Features:

- 4 adjustable set point temperatures
- Operates auto flush
- Last temperature memory
- 45 minute timer
- All metal construction, not plastic

Deluxe Steamhead

- Dispenses steam safely
- Aromatherapy well



4-1/2" x 3-9/16" x 3/4"



1-1/2" x 1-1/4" x1 1/2"

CONTROL KIT STSC-OSS-XX*

Available in PC, PN, SN, ORB

Control Features:

- Day Clock
- Set time
- Set temperature
- Operates auto flush
- Last setting memory
- · All metal construction, not plastic

Deluxe Steamhead

- Dispenses steam safely
- Aromatherapy well

*Select desired finish and replace XX with code: PC: Polished Chrome PN: Polished Nickel SN: Satin Nickel ORB: Oil Rubbed Bronze

