MOEN®

FAUCET DESCRIPTION

- Reflex[™] pulldown system offers smooth operation, easy movement and secure docking
- Metal construction with various finishes identified by suffix
- High arc spout provides the height and reach to fill or clean large pots while the pulldown feature provides the infinite maneuverability for cleaning or rinsing
- Duralock[™] quick connect installation
- Pulldown spray with 68" braided hose
- High arc spout provides height and reach to fill or clean large pots while pullout wand provides the maneuverability for cleaning or rinsing
- 360° rotating spout
- Flexible supply lines with 3/8" compression fittings Power Boost™ Spray Technology

OPERATION

- Temperature controlled by 100° arc of handle travel When filling a vessel outside of the sink, the pause feature conveniently
- stops the flow of water as the wand passes over the countertop Convenient single-button actuation provides flexibility to switch from stream to spray mode FLOW

- Flow is limited to 1.5 gpm (5.7 L/min) at 60 psi
- CARTRIDGE
- 1255[™] Duralast[™] cartridge STANDARDS
- Third party certified to IAPMO Green, ASME A112.18.1/CSA B125.1 and all appli-
- cable requirements therein including NSF 61/9 & 372
- Meets CalGreen and Georgia SB370 requirements
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act The backflow protection system in this device consists of two independently
- operating check valves, a primary and a secondary which prevent backflow
- ADA (L for lever handle

WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original homeowner
- 10 year limited warranty when used in a multifamily installation
- 5 year limited warranty when used in a commercial installation
- Visit www.moen.com/support for complete details and limitations



SLEEK[™] Single Handle High Arc Pulldown **Kitchen Faucet**

Model: 7871 series

NOTE: DESIGNED TO INSTALL THROUGH 2 HOLES 1-1/4" (32mm) MIN. DIA.



5-3/4"

