

PSI Rating	0 – 120 PSI
Hose Length	26"
Gauge Accuracy	+/- 3%
Duty Cycle	50% at 10 Minutes On and 10 Minutes Off
Height / Weight	7.5" / 2.2 lbs



Air Volume	33 CFM
Suction (H ₂ O)	14.5"
Run-Time (XC4.0)	Up to 29 mins
Inlet Diameter	1-1/4"
Weight	2.3 lbs

A red Milwaukee M18 4-Bay Battery Charger is shown. It has four slots for M18 batteries, each with a grey and black battery pack inserted. The charger has a black top with four indicator lights and a red base with the Milwaukee logo.

Compatibility	All M12™ Batteries
Charge Sequence	Sequential (First In, First Charged)
Integrated Hang-Holes	Yes
Skip Button	Manually Designate which Battery Charges First
On-Board Indicator Light	Yes
Cell Voltage Monitoring	Yes



Compatibility	All M18™ and M12™ Batteries
Charge Sequence	Charges 3 Batteries Simultaneously
Charge Speed	Charges Individual Batteries up to 40% Faster
Capacity	Holds (3) M18™ and (3) M12™ Batteries
Integrated Hang-Holes	Yes
Cell Voltage Monitoring	Yes
Pass-Through Plug	Yes

Pass-Through Plug

A red and black power supply unit, likely a car battery charger or a power source for a portable device. It features a digital display screen showing the number '12.0' and a power button. The unit is connected to a black cable.

Compatibility	All M18™ and M12™ Batteries
Charge Sequence	Sequential (First In, First Charged)
Charge Speed	Charges Individual Batteries up to 40% Faster
On-Board Indicator Light	Yes
Integrated Hang-Holes	Yes
Cell Voltage Monitoring	Yes



Compatibility	All M18™ and M12™ Batteries
Charge Sequence	Sequential (First In, First Charged)
Integrated Hang-Holes	Yes
On-Board Indicator Light	Yes
Cell Voltage Monitoring	Yes

Compatibility	All M18™ and M12™ Batteries
Charge Sequence	Sequential (First In, First Charged)
On-Board Indicator Light	Yes
Cell Voltage Monitoring	Yes



A red and grey Milwaukee M12 FUEL SYSTEM Lithium-Ion Battery Pack is shown next to its black and red charger. The battery has the Milwaukee logo and 'M12 FUEL SYSTEM' printed on it. The charger has a standard two-prong electrical plug.

Compatibility	All M12™ Batteries
USB Charging Port	2.1A USB Charging Port for External Devices
On-Board Indicator Light	Yes
Cell Voltage Monitoring	Yes
Charges By	USB Port or AC Outlet

Compatibility	All M12™ Batteries
Integrated Hang-Holes	Yes
On-Board Indicator Light	Yes
Cell Voltage Monitoring	Yes

Battery Sold Separately

UPGRADE. OUTWORK. OUTLAST.

UP TO
3X
MORE
RUN-TIME

UP TO
20%
MORE
POWER

OVER
2X
MORE
LIFE



REDLITHIUM
CP3.0/XC6.0

M12 REDLITHIUM™ BATTERIES GUIDE

Less weight
and smaller size



More power
and run-time



48-11-2430
M12™ REDLITHIUM™
CP3.0 Battery Pack



48-11-2460
M12™ REDLITHIUM™
XC6.0 Battery Pack



48-11-2420
M12™ REDLITHIUM™
CP2.0 Battery Pack



48-11-2440
M12™ REDLITHIUM™
XC4.0 Battery Pack



48-11-2401
M12™ REDLITHIUM™
CP1.5 Battery Pack

48-11-2411
2-Pack



48-11-2402
M12™ REDLITHIUM™
XC3.0 Battery Pack

48-11-2412
2-Pack