

CIRCULAR SAW BLADES

WOOD CUTTING CIRCULAR SAW BLADES

OVERVIEW

MILWAUKEE® Circular Saw Blades provide longer life, increased accuracy and cooler cuts in wood cutting applications. The blades are designed utilizing application-specific Cobalt Infused Tungsten Carbide to extend cutting life and maintain tip sharpness. The blades feature Laser Cut Vibration Slots to reduce wobble and warping. With an Anti-Friction Coating, the blades resist corrosion and gummying. MILWAUKEE's Circular Saw Blades are optimized for cordless and corded performance.

FEATURES

- Cobalt Infused Tungsten Carbide: Extends cutting life and maintains tip sharpness
- Anti-Friction Coating: Provides cooler cuts
- Laser Cut Vibration Slots: Increase blade accuracy and prevent wobble and warping



CARBIDE TEETH

WOOD CUTTING CIRCULAR SAW BLADES

Diameter	No. of Teeth	Application	Hook Angle	Kerf Thickness (mm)	Arbor Size	Part No.	Bulk 10
5-3/8"	16	Framing	15°	0.063	10 mm	48-40-0522	–
5-3/8"	36	Finish	15°	0.063	10 mm	48-40-0524	–
5-1/2"	18	Framing	18°	0.063	10 mm	48-40-0520	–
6-1/2"	24	Framing	18°	0.063	5/8", 	48-40-0620	48-41-0620
6-1/2"	40	Finish	15°	0.063	5/8", 	48-40-0622	–
7-1/4"	24	Framing	20°	0.063	5/8", 	–	48-41-0710
7-1/4"	24	Framing	20°	0.063	5/8", 	–	48-41-0713
7-1/4"	24	Framing	18°	0.063	5/8", 	48-40-0720	48-41-0720
7-1/4"	24	Framing	18°	0.063	5/8", 	–	48-41-0723
7-1/4"	40	Finish	15°	0.063	5/8", 	48-40-0726	48-41-0726
7-1/4"	60	Finish	15°	0.063	5/8", 	48-40-0730	48-41-0730
8-1/4"	24	Framing	18°	0.083	5/8", 	48-40-0820	–
8-1/4"	40	Finish	15°	0.083	5/8", 	48-40-0822	–
8-1/4"	60	Finish	12°	0.094	5/8"	48-40-0826	–
8-1/2"	40	General Purpose	15°	0.094	5/8"	48-40-0824	–
10"	24	Ripping	22°	0.094	5/8"	48-40-1020	–
10"	40	General Purpose	15°	0.094	5/8"	48-40-1024	–

WOOD CUTTING CIRCULAR SAW BLADES

Diameter	No. of Teeth	Application	Hook Angle	Kerf Thickness (mm)	Arbor Size	Part No.	Bulk 10
10"	50	Combination	12°	0.094	5/8"	48-40-1026	–
10"	60	Finish	12°	0.094	5/8"	48-40-1028	–
10"	80	Finish	12°	0.094	5/8"	48-40-1032	–
10"	40 & 60	General Purpose/Finish	15° & 12°	0.094 & 0.094	5/8"	48-40-1036	–
10-1/4"	28	Framing	18°	0.102	5/8"	48-40-1038	–
10-1/4"	40	Finish	12°	0.102	5/8"	48-40-1040	–
12"	44	General Purpose	15°	0.118	1"	48-40-1220	–
12"	60	Combination	12°	0.118	1"	48-40-1222	–
12"	80	Finish	12°	0.118	1"	48-40-1224	–
12"	100	Finish	12°	0.118	1"	48-40-1228	–
12"	44 & 80	General Purpose/Finish	15° & 12°	0.118 & 0.118	1"	48-40-1232	–

METAL CUTTING CIRCULAR SAW BLADES

OVERVIEW

MILWAUKEE® Metal Cutting Circular Saw Blades were specifically designed to exceed contractors expectations for blade life, cut quality and speed in the most demanding metal cutting applications – without a lubricant. A hand-tensioned, hardened alloy steel body minimizes vibration to extend blade life and delivers the highest quality cuts available. Carbide teeth shear through metal leaving burr-free, cool-to-touch cuts.

FEATURES

- Dry: No lubricant required, saving time and money with less mess
- Cool: No extreme heat buildup preserves blade life and allows handling the work piece immediately
- Clean: No burrs eliminates secondary operations, saving time and money



CARBIDE TEETH

METAL CUTTING CIRCULAR SAW BLADES

Diameter	No. of Teeth	Application	Hook Angle	Kerf Thickness	Arbor	Part No.
5-3/8"	30	Metal and Stainless	0°	0.063"	20 mm	48-40-4070
5-3/8"	30	Metal and Stainless	0°	0.063"	5/8"	48-40-4205
5-7/8"	34	Metal	2°	0.063"	20 mm	48-40-4215
6-1/2"	48	Metal	2°	0.063"	5/8"	48-40-4220
6-7/8"	36	Metal	2°	0.063"	20 mm	48-40-4225
7	40	Metal	2°	0.071"	20 mm	48-40-4230
7-1/4"	48	Metal	2°	0.071"	5/8"	48-40-4235

Diameter	No. of Teeth	Application	Hook Angle	Kerf Thickness	Arbor	Part No.
7-1/4"	48	Metal	2°	0.071"	20 mm	48-40-4237
7-1/4"	70	Thin Metal	-5°	0.071"	5/8"	48-40-4240
8"	42	Metal and Stainless	0°	0.073"	5/8"	48-40-4515
8"	50	Thin Metal and Stainless	0°	0.073"	5/8"	48-40-4520
9"	48	Metal	0°	0.071"	1"	48-40-4255
10"	50	Metal	0°	0.079"	5/8"	48-40-4260
12"	60	Metal	0°	0.087"	1"	48-40-4265