



3/4" HEX CHISELS

| Tip Type                                                                          | Style             | Application                               | Size                               | Part No.   |
|-----------------------------------------------------------------------------------|-------------------|-------------------------------------------|------------------------------------|------------|
|  | Clay Spade        | Digs up clay, hard-packed gravel and dirt | 4-1/2" x 16-3/4"                   | 48-62-3040 |
|  | Ground Rod Driver | Drives soft ground rods                   | 9-3/4"L - 5-8" & 3/4" Rod Diameter | 48-62-3070 |
|  | Tamper Shank      | Used to mount tamper plate                | 12"                                | 48-62-3065 |
|  | Tamper Plate      | Compacts dirt, tamps asphalt              | 5" x 5"                            | 48-62-3060 |

1-1/8" HEX

1-1/8" HEX DEMOLITION STEEL



1-1/8" HEX DEMOLITION STEEL

| Tip Type                                                                            | Style              | Application                                                   | Size          | Part No.   |
|-------------------------------------------------------------------------------------|--------------------|---------------------------------------------------------------|---------------|------------|
|  | Moil Point         | Starts holes in concrete slabs, general chipping and breaking | 16"           | 48-62-4001 |
|                                                                                     | Moil Point         |                                                               | 20"           | 48-62-4000 |
|  | Narrow Chisel      | General chipping and breaking                                 | 16"           | 48-62-4006 |
|                                                                                     | Narrow Chisel      |                                                               | 20-1/2"       | 48-62-4005 |
|  | Scaling Chisel     | Cleans concrete, scale, rust, cuts troughs and some asphalt   | 3" x 20-1/2"  | 48-62-4010 |
|  | Asphalt Cutter     | Cuts asphalt or hard ground (DO NOT use for concrete)         | 5" x 17-1/2"  | 48-62-4020 |
|  | Clay Spade         | Digs up clay, hard-packed gravel and dirt                     | 5-1/2" x 20"  | 48-62-4030 |
|  | Ground Rod Driver  | Drives soft ground rods                                       | 15-1/2"L x 3" | 48-62-4045 |
|  | Spike & Pin Driver | Drives anchoring pins for concrete forms                      | 14-1/2"       | 48-62-4040 |
|  | Tamper Shank       | Used to mount tamper plate                                    | 6" x 6"       | 48-62-4060 |

1-1/8" HEX DEMOLITION STEEL

| Tip Type                                                                            | Style                         | Application                                        | Size                             | Part No.   |
|-------------------------------------------------------------------------------------|-------------------------------|----------------------------------------------------|----------------------------------|------------|
|  | Tamper Plate                  | Compacts dirt, tamps asphalt (Use with 48-62-4060) | 6" x 6"                          | 48-62-4050 |
|                                                                                     | Tamper Plate                  |                                                    | 8" x 8"                          | 48-62-4055 |
|  | Tent Stake Driver – Head Only | Drives in large tent stakes (Use with 48-62-4060)  | 5-1/2" L / 3-1/2" OD / 2-3/4" ID | 48-62-4061 |

CARBIDE HAMMER DRILL BITS

OVERVIEW

MILWAUKEE® Carbide Hammer Drill Bits use sharpened carbide, delivering up to 5X life in concrete and up to 2X faster drilling. Engineered with a precision ground tip, these bits will deliver faster starts and less walking in concrete, brick, block and masonry. Wide flute design removes dust faster, reducing heat and delivering more holes per charge. The extended life of the MILWAUKEE® Carbide Hammer Drill Bits provides the ideal solution in concrete, brick and block for cordless and corded hammer drill/drivers.

FEATURES

- Up to 5X life in concrete
- Up to 2X faster versus standard masonry bits
- Durable Carbide Tip: Longer life in concrete and hard aggregate

CARBIDE HAMMER DRILL BITS

| Diameter | Usable Length | Length | Shank Type             | 1 Pack     | 5 Pack     | 25 Pack    |
|----------|---------------|--------|------------------------|------------|------------|------------|
| 1/8"     | 2"            | 3-1/2" | SHOCKWAVE Impact Duty™ | 48-20-9000 | –          | 48-20-9100 |
| 5/32"    | 4"            | 6"     | SHOCKWAVE Impact Duty™ | 48-20-9001 | 48-20-9155 | 48-20-9101 |
| 3/16"    | 2"            | 4"     | SHOCKWAVE Impact Duty™ | 48-20-9005 | –          | 48-20-9105 |
| 3/16"    | 4"            | 6"     | SHOCKWAVE Impact Duty™ | 48-20-9006 | 48-20-9157 | 48-20-9106 |
| 7/32"    | 4"            | 6"     | SHOCKWAVE Impact Duty™ | 48-20-9009 | –          | –          |
| 1/4"     | 2"            | 4"     | SHOCKWAVE Impact Duty™ | 48-20-9010 | –          | 48-20-9110 |
| 1/4"     | 4"            | 6"     | SHOCKWAVE Impact Duty™ | 48-20-9011 | 48-20-9162 | 48-20-9111 |
| 1/4"     | 10"           | 12"    | 3-Flat                 | 48-20-9012 | –          | –          |
| 5/16"    | 4"            | 6"     | SHOCKWAVE Impact Duty™ | 48-20-9016 | –          | 48-20-9116 |
| 5/16"    | 8"            | 10"    | 3-Flat                 | 48-20-9018 | –          | –          |
| 5/16"    | 10"           | 12"    | 3-Flat                 | 48-20-9017 | –          | –          |
| 3/8"     | 4"            | 6"     | SHOCKWAVE Impact Duty™ | 48-20-9021 | –          | 48-20-9121 |
| 3/8"     | 10"           | 12"    | 3-Flat                 | 48-20-9022 | –          | –          |
| 3/8"     | 16"           | 18"    | 3-Flat                 | 48-20-9023 | –          | –          |
| 7/16"    | 4"            | 6"     | SHOCKWAVE Impact Duty™ | 48-20-9025 | –          | 48-20-9125 |
| 1/2"     | 4"            | 6"     | SHOCKWAVE Impact Duty™ | 48-20-9030 | –          | 48-20-9130 |
| 1/2"     | 10"           | 12"    | 3-Flat                 | 48-20-9031 | –          | –          |
| 1/2"     | 16"           | 18"    | 3-Flat                 | 48-20-9032 | –          | –          |
| 9/16"    | 4"            | 6"     | 3-Flat                 | 48-20-9035 | –          | –          |



UP TO  
**5x**  
LIFE  
IN CONCRETE