MOEN®

Specifications

DESCRIPTION

- One piece, cast brass construction above-deck with various finishes identified by suffix
- Modern Style matches M•Power[™] lav (model 8559)
- Single mount
- Easily refillable 1500mL foam soap reservoir included
- Works with all commercial, non-pumice foam soaps (purchased separately)
- Vandal resistant below-deck box with included mounting hardware
- Do not install or operate at temperatures below 32°F (0°C)

OPERATION

- "Touch free" operation for improved hygiene
- Adjustable sensor activation distance
- One ~1mL dispense per activation
- Maintenance/Cleaning Mode: Allows for a 30 second deactivation for maintenance or cleaning
- Low battery, low soap, and service indicator LED's
- (4) D batteries (included) with AC compatibility
- For AC connection: Transformer 104630 required for up to 8 devices, and 182538 connector for each device
- Battery life: 1 year or 50,000 cycles

STANDARDS

- Meets the current requirements of the Buy American Act (BAA)
- ADA 🕭 compliant
- Third party certified to meet FCC part 15

WARRANTY

• Warranted for 5 years against material or manufacturer defects

NOTES

- Caution: Do not kink Soap Tube
- Ensure Pump Assembly is centered under Spout
- Soap may take up to approximately 20 dispense cycles to switch from liquid to foam form after installation.
- Soap dispenser may not operate with sinks that protrude above the deck mounting surface. Consult the Exploded Parts View for spacers that may be used in some of these installations.



M•Power™ Align® Style Electronic Soap Dispenser

Models: 8560 Series

NOTE: THIS FAUCET IS DESIGNED TO BE INSTALLED THROUGH 1 HOLE, 1" MIN. DIA.




Refer to back for dimensions

3(0)/2021

MOEN®

Specifications



03/09/2021 SPC14758 50000348156 Released 01