

TOUGH

BEYOND MEASURE™

THE NEW DEWALT® XP™ TAPE MEASURE

TOUGHER
CASE*



TOUGHER
BLADE COATING*



TOUGHER
HOOK CONNECTION*



DEWALT®

GUARANTEED TOUGH.®

DEWALT®

TAPE MEASURES



*TOUGHER CASE, TOUGHER BLADE COATING, TOUGHER HOOK CONNECTION CLAIMS BASED ON COMPARISONS TO DWHT36107, DWHT36109, DWHT36105, DWHT33976L, DWHT33976, DWHT33975, DWHT36027

©2017 DEWALT Industrial Tool Co.

MKT-2754
DWHTTAPEFAMBR

GUARANTEED TOUGH.®



13' STRAIGHTER STANDOUT**



- **Greater Durability**
Survives a 60' drop***
- **9" Heavy-Duty Thermoplastic Coating**
Maximizes blade life and helps reduce blade breakage



13' STANDOUT



- **Reinforced Housing And Metal Impact Plate**
For blade hook protection and longer life
- **3" Heavy-Duty Thermoplastic Coating**
Reduces blade breakage near the hook



10' STANDOUT

- **Wide Base**
For stability when standing
- **Fractional Blade**
For quick and easy measurements



DEWALT® TAPE MEASURES

SKUS	DWHT36225 (25'), DWHT36226 (8m/26'), DWHT36235 (35')	DWHT33972 (16'), DWHT33975 (25'), DWHT33991 (8m/26'), DWHT33976 (35')	DWHT36105 (16'), DWHT36107 (25'), DWHT36027 (8m/26'), DWHT36109 (30')
TAPE	DEWALT® XP™ 1-1/4"	DEWALT® 1-1/4"	DEWALT® 1-1/8"
BLADE COATING	NEW DEWALT® XP Protective Film	Mylar®	Tylon™ (Lacquer)
HOOK REINFORCEMENT	9"	3"	N/A
SLIDE LOCK	Plastic and Rubber	Plastic and Rubber	Plastic and Rubber
LANYARD SLOT	Yes	Yes	Yes
HOUSING CONSTRUCTION	High-Impact ABS Reinforced with Polycarbonate and Rubber Overmold	High-Impact ABS and Rubber Overmold	High-Impact ABS and Rubber Overmold
HEIGHT	3-1/8" (79 mm)	3-1/4" (83 mm)	3-3/16" (81 mm)
PRINTING	Standard	Standard	Fractional (Excluding Metric/Imperial Scale)
COUNTRY OF ORIGIN	USA with Global Materials	USA with Global Materials	Thailand