

OPTIONS**Flush Volume**

- 0.5 gpf (1.9 Lpf) (0.5)
- 0.25 gpf (0.9 Lpf) (0.25)
- 1.0 gpf (3.8 Lpf) (1.0)
- 1.5 gpf (5.7 Lpf) (1.5)
- 0.125 gpf (0.5 Lpf) (0.125)

Finish

- Polished Chrome (CP)

Activation

- Manual

Valve

- Piston

Water Efficiency

- High Efficiency
- Low Consumption
- Water Saver

Fixture Type

- Urinal

Fixture Connection

- Top Spud

Installation

- Exposed

Control Stop

- 1" (1-IN-STOP)
- Ground Joint (GJ)

Vacuum Breaker

- Less (XYV)

Adapter

- XL Sweat Solder Adapter Kit (XL)

Compliances & Certifications

- BAA Compliant
- cUPC Certified
- ADA Compliant
- WaterSense Listed
- BREEAM Water Credit
- EPD
- Green Globes Water Credit
- HPD
- LEED V4 Water Efficiency Credit
- Satisfies LEED Credits



Image for a standard GEM-2 186 shown

DESCRIPTION

GEM-2® Exposed Manual Urinal Flushometer

FEATURES

- Flush volumes start at 0.125 gpf/0.5 Lpf
- Fixed volume piston with filtered O-ring bypass and ADA-compliant, metal oscillating, non-hold-open handle ensure reliable, water-efficient operation
- Integrity of the product is maintained with control stop plug
- Durability is facilitated with high copper, low zinc brass castings for dezincification resistance and components made from PERMEX™ rubber compound for chloramine resistance
- Adjustable tailpiece
- Valve body, Cover, Tailpiece and Control Stop shall be in compliance with ASTM Alloy Classification for Semi-Red Brass
- Valve shall be in compliance to the applicable sections of ASSE 1037.

DOWNLOADS

- [GEM/GEM 2 Piston Type Exposed Installation Instructions](#)
- [Control Stop Repair and Maintenance Guide](#)
- [Flush Connections Flanges Repair and Maintenance Guide](#)
- [Tail Piece Repair and Maintenance Guide](#)
- [Gem 2 Repair and Maintenance Guide](#)
- [Additional Downloads](#)

Sloan 10500 Seymour Ave, Franklin Park, IL 60131

Phone: 800.982.5839 • Fax: 800.447.8329 • sloan.com

NOTES

For product line drawings, [view model-specific spec sheets](#).

All information contained within this document subject to change without notice.