



## FOR YOUR SAFETY READ BEFORE OPERATING



### WARNING: Fire or Explosion Hazard.

Can cause property damage, severe injury or death. Force or attempted repair may result in a fire or explosion. Follow these instructions exactly.

- A. This appliance is equipped with an ignition device which automatically lights the pilot or burner. Do not try to light the pilot or burner by hand.
- B. BEFORE LIGHTING smell all around the appliance area for gas. Be sure to smell next to the floor because some gas is heavier than air and will settle on the floor.

#### WHAT TO DO IF YOU SMELL GAS



- Do not try to light any appliance.
- Do not touch any electric switch; do not use any phone in your building.
- Immediately call your gas supplier from a neighbor's phone. Follow the gas supplier's instructions.

- If you cannot reach your gas supplier, call the fire department.
- C. Use only your hand to push in or turn the gas control knob or slide the gas control switch to "ON." Never use tools. If the knob or switch will not push in or turn by hand, don't try to repair it; call a qualified service technician. Force or attempted repair may result in a fire or explosion.
- D. Do not use this appliance if any part has been under water. Immediately call a qualified service technician to inspect the appliance and to replace any part of the control system and any gas control which has been under water.

## OPERATING INSTRUCTIONS

1. STOP! Read the safety information above on this label.
2. Set the thermostat to lowest setting.
3. Turn off all electric power to the appliance.
4. This appliance is equipped with an ignition device which automatically lights the pilot or burner. Do not try to light the pilot or burner by hand.
5. Remove control access panel.
6. Turn gas control knob clockwise  or slide gas control switch to "OFF."

7. Wait five (5) minutes to clear out any gas. If you then smell gas, STOP! Follow "B" in the safety information above on this label. If you don't smell gas, go to the next step.
8. Turn gas control knob counterclockwise  or slide gas control switch to "ON."
9. Replace control access panel.
10. Turn on all electric power to the appliance.
11. Set thermostat to desired setting.
12. If the appliance will not operate, follow the instructions "To Turn Off Gas To Appliance" and call your service technician or gas supplier.



SV9510 SV9540 SV9570 SV9620 SV9660  
SV9520 SV9560 SV9610 SV9640 SV9670

M12430

## TO TURN OFF GAS TO APPLIANCE

1. Set the thermostat to lowest setting.
2. Turn off all electric power to the appliance if service is to be performed.
3. Remove control access panel.
4. Turn gas control knob clockwise  to "OFF" or slide gas control switch to "OFF." Do not force.
5. Replace control access panel.

## MOUNTING INSTRUCTIONS

1. Choose a location on the furnace cabinet where the lighting instructions will be readily visible when the pilot is being lit.
2. Remove the paper backing.
3. Line up the top edge of the sticker so it looks straight and press down the edge. Roll the sticker down from the top, smoothing it with your hand and removing air bubbles as you go.
4. Rub your hand gently over the entire sticker to make sure it is firmly attached to the furnace cabinet.
5. Discard the paper backing.



Resideo Technologies, Inc.  
1985 Douglas Drive North, Golden Valley, MN 55422

[www.resideo.com](http://www.resideo.com) 69-0373-02 M.S. Rev. 05-20 | Printed in United States

© 2020 Resideo Technologies, Inc. All rights reserved.  
This product is manufactured by Resideo Technologies, Inc. and its affiliates.