

Cable Stapler Instructions
Instrucciones para engrapadora para cable (ver otro lado)
Instructions pour l'agrafeuse de câble (voir de l'autre côté)

FEATURE DETAILS / DETALLES DE LAS CARACTERÍSTICAS / CARACTÉRISTIQUES DÉTAILLÉES



ENGLISH

- 1 Cushioned handle
- 2 Tension Setting Lever
- 3 Staple Push Rod
- 4 Push Rod Release Latch
- 5 Belt Clip*
- 6 Staple / Cable Size Selector
- 7 Staple Discharge Area
- 8 Locking Buttons
- 9 Cable Guides
- 10 Actuation Force
- 11 Belt Clip Mounting Recess* (x2)

*Belt clip can be mounted on either side of stapler. To switch sides, remove #2 Phillips screw, lift clip and bracket, and move to mounting recess on opposite side. Place clip and bracket and screw into place and secure by firmly tightening the screw into place. Use manual screwdriver only; do not overtighten.

ESPAÑOL

- 1 Mango acojinado
- 2 Palanca de ajuste de tensión
- 3 Empujador de grapas
- 4 Bloqueo de liberación del empujador
- 5 Clip para cinturón*
- 6 Selector de tamaño de grapa/cable
- 7 Área de descarga de grapas
- 8 Botones de bloqueo
- 9 Guías de cable
- 10 Fuerza de accionamiento
- 11 Ranura para fijar el clip para cinturón* (2)

*El clip para cinturón puede fijarse en cualquier lado de la engrapadora. Para cambiar de lado, retire el tornillo Phillips n.º 2, levante el clip y el soporte y fíjelo en la ranura del lado opuesto. Ubique el clip, soporte y tornillo en sus lugares y asegure ajustando firmemente el tornillo. Utilice solamente un desarmador, no apriete demasiado.

FRANÇAIS

- 1 Manche coussiné
- 2 Levier de réglage de la tension
- 3 Poussoir des agrafes
- 4 Loquet de dégagement du poussoir
- 5 Pince pour ceinture*
- 6 Sélecteur de la taille des agrafes et des câbles
- 7 Zone de décharge des agrafes
- 8 Boutons de verrouillage
- 9 Guide-câble
- 10 Force d'actionnement
- 11 Encoche de montage de la pince pour ceinture* (x2)

* La pince pour ceinture peut être installée de chaque côté de l'agrafeuse. Pour la changer de côté, retirez la vis à tête cruciforme n° 2, soulevez la pince et son ancrage et déplacez-les dans l'encoche de montage du côté opposé. Tenez la pince et son ancrage en place, puis fixez-les en serrant fermement la vis. Utilisez uniquement un tournevis manuel; ne serrez pas trop fort.



FIG. 3



ENGLISH

The Klein Tools Cable Stapler features a forward action for greater stability. It is designed to allow user to push the handle, rather than squeeze, delivering easy, consistent performance. The staples are released from the front end of stapler, nearest to where the handle is pressed down. A cable guide along the entire bottom surface protects the cable from being crushed during the stapling process.

⚠ WARNINGS

Read all instructions thoroughly prior to use. Failure to read, understand, and follow all instructions may result in serious injury.

- Never work on or near live electric circuits.
- Always wear approved eye protection and hearing protection.
- Keep fingers clear of staple discharge area when operating or clearing a jam.
- Only direct staple discharge towards surface intended to be stapled; never point towards any body part.
- Ensure correct staple size is selected before discharging.
- Use proper positioning of the cable guide to prevent staples from piercing the cable
- Always be cautious of potential hazards such as electrical wiring, damp or wet conditions, unstable surfaces.
- For professional use only.
- Keep away from children.

⚠ WARNING SYMBOLS ON PRODUCT

- ⚠ Warning or caution
- 👁 Always wear approved eye protection
- 👂 Do not use on live electric circuits
- 👂 Always wear approved hearing protection
- 📖 Read instructions before using

OPERATING INSTRUCTIONS

NOTE: Use only on wood frames / structures of low or medium density. Hard woods may cause malfunction or partial staple penetration. Always ensure proper staple size is loaded in cable stapler.

STAPLE SELECTION (FIG. 1, FIG. 2):

⚠ WORKS EXCLUSIVELY WITH KLEIN TOOLS STAPLES. NOT COMPATIBLE WITH OTHER BRANDS OF STAPLES.

Determine appropriate staple size for cable type (see staple size guide on side of stapler):

- **450-001** - 1/4" for: CAT3, CAT5e, or speaker wire
- **450-002** - 5/16" for: CAT3, CAT5e, or CAT6/6A, Coax
- **450-003** - 19/32" for: NM: 14/3, 14/3G, 12/3, Qty 1 or 2 Coax, or Qty 1 to 3 CAT3/5e/6/6A
- **450-004** - 31/64" for: NM: 14/2, 14/2G, 10/2, 10/2G, or Qty 1 or 2 speaker wires

For use with 450-001 or 450-002: Ensure the Staple / Cable Size Selector (6) is in the down position (FIG. 1). If it is in the up position, grasp staple guide firmly and pull down until locked. The Staple / Cable Size Selector (6) is locked in the down position when the Locking Buttons (8) are fully released.

For use with 450-003 or 450-004: Ensure the Staple / Cable Size Selector (6) is in the up position (FIG. 2). If it is in the down position, depress both Locking Buttons (8) (on both sides of stapler), and slide the Staple / Cable Size Selector (6) to the up position. Ensure that the cable opening is fully exposed.

STAPLE TENSION ADJUSTMENT:

For use with 450-001 and 450-002: Tension Setting Lever (2) should be in the lower tension, down position.

For use with 450-003 and 450-004: Tension Setting lever (2) should be in the higher tension, up position.

To change between positions, push in and turn gently. For reference, the higher tension setting may be necessary when using the 450-001 and 450-002 with harder woods, and the lower tension may be necessary when using 450-003 and 450-004 on softer materials, such as drywall. Perform a test setting determination on a non-visible surface.

LOADING STAPLES:

1. Hold staple gun upside down, depress Push Rod Release Latch (4), pull out Staple Push Rod (3).
2. Insert appropriate staple, with the legs pointing up (FIG. 3).
3. Firmly push the Push Rod Release Latch (4) closed.

NOTE: DO NOT mix staples of different sizes. Partial strips, damaged strips or mixing of different sized staples may jam the stapler.

STAPLING CABLE:

1. Locate stapler over cable, ensuring cable is contained within the Cable Guides (9) for entire length of stapler, front to back.
2. Press Handle (1) firmly downward to release staple.
3. If staples jam, ensure that you are using the proper staple size and tension setting. Also ensure that you are not attempting to staple into a surface that cannot be penetrated by a staple. In the event of a jam, clear jammed staple gently, wearing gloves to prevent injury to hands.

WARRANTY

www.kleintools.com/warranty

CUSTOMER SERVICE

KLEIN TOOLS, INC.
450 Bond Street Lincolnshire, IL 60069 1-877-775-5346
customerservice@kleintools.com www.kleintools.com

