

B
Sanding / Polishing Pads & Bonnets

Description	Grinder/Polisher Size	Model	Part #	Description	Grinder/Polisher Size	Model	Part #
 20 Rubber Pad	4"	GA4030/K	743009-6	 7" Wool Bonnet Tie Back	7"	9227C/CY, 9237C, PV7001C	794176-0
	4"	PW5001C	743079-5				
	4-1/2"	9557NB/PB, 9564CV/P/PC, GA4530, GA4534, XAG01, XAG03, XAG06	743036-3	 7" Hook-and-Loop Pad Compounding	7"	9227C/CY, 9237C, PV7001C	192629-7
	5"	9005B/BZ, 9015A, 9565CV/PC, GA5010Z, GA5020/Y	743015-1				
	6"	9566CV/PC, GA6010, GA6020	743016-9	 7" Hook-and-Loop Pad Polishing	7"	9227C/CY, 9237C, PV7001C	743403-A
 Plastic Pad	5"	GA7001L, GA7911, GV7000C, 9077SL, 9218SB, 9227C, 9227CY, 9237C, GA7011C, GA7020, GA7021, GA7040S	192978-2				
	7", 9"			 7-1/2" Hook-and-Loop Foam Pad Polishing	7"	9227C/CY, 9237C, PV7001C	193470-1
Hook-and-Loop Backing Pad	5"	GV5000, GA5010	743025-8				
	7"	9227C/CY, 9237C, PV7001C	743052-5				

C
Wire Brushes

Description	Diameter	Arbor	Max.Safe RPM	Model	Carbon Steel Part #	Stainless Steel Part #
 Crimped Cup • Excellent for flat surfaces, edges, paint, scale, light rust removal • Use with spindle mount washer (261039-0)	3"	M10 x 1.25	14,000	GA4030	743201-4	
	3"	5/8" - 11	14,000	9005B/BZ, 9557NB/PB, 9558PB, 9564CV/PC, 9565CV/PC, GA4530, GA4534, GA5010Z, GA5020/Y	743205-6	
	4"	5/8" - 11	10,000	9566CV, GA7001L, GA7011C, GA7040S	743207-2	
	6"	5/8" - 11	6,600	GA7001L, GA7011C, GA7020, GA7021, GA9020, GA9040S	743206-B	
 Knot Cup • Ideal for tight operations, corners and angle welds. Rugged knot construction • .020" Type 302 Stainless Steel Wire is corrosion resistant • Use with spindle mount washer (261039-0)	2-3/4"	M10 X 1.25	14,000	GA4030	743201-5A	743204-A
	2-3/4"	5/8" - 11	14,000	9005B/BZ, 9557NB/PB, 9558PB, 9564CV/PC, 9565CV/PC, GA4530, GA4534, GA5010Z, GA5020/Y	743209-A	743209-B
	4"	5/8" - 11	10,000	9564CV/PC/P, 9565CV/PC, 9566CV/PC, GA7001L, GA7011C, GA7020, GA7021, GA7040S	743208-0A	
	6"	5/8" - 11	6,600	GA7001L, GA7011C, GA7020, GA7021, GA9020, GA9040S, GA9040S	743206-A	

C
Wire Wheels

Description	Diameter	Arbor	Max.Safe RPM	Model	Carbon Steel Part #	Stainless Steel Part #
 Stringer Bead Twist Wheel • 3/16" face width for stringer weld, piping, pipe grooves & hard to reach areas • .020" Type 302 Stainless Steel Wire is highly corrosion resistant	4"	M10 x 1.25	20,000	GA4030	743203-5A	743204-B
	4"	5/8" - 11	20,000	9005B/BZ, 9557NB/PB, 9558PB, GA4530, GA4534, GA5010Z, GA5020/Y	743213-A	743213-B
	5"	5/8" - 11	12,500	9005B/BZ, 9557NB/PB, 9558PB, GA7001L, GA7011C, GA7020/21, GA9020, GA9040S	743216-A	
 Knot Full Cable Twist Wheel • 1/4" face width for narrow to medium width work. Excellent for cleaning welds • .020" Type 302 Stainless Steel Wire is highly corrosion resistant	4"	M10 X 1.25	20,000	GA4030		743203-4B
	4"	5/8" - 11	20,000	9564CV/PC/P, 9565CV/PC, 9566CV/PC, GA7001L, GA7011C, GA7020, GA7021, GA7040S	743211-A	743214-A
	5"	5/8" - 11	12,500	9564CV/PC/P, 9565CV/PC, 9566CV/PC, GA7001L, GA7011C, GA7020, GA7021, GA7040S	743217-A	
 Knot Standard Twist Wheel • 1/2" face width for broader cleaning coverage. For deburring, edge blending & finishing. • Removes rust, scale & weld splatter	6"	5/8" - 11	12,500	GA7001L, GA7011C, GA7020, GA7021, GA7040S, GA9020, GA9040S	743218-A	
	4"	M10 X 1.25	20,000	GA4030	743203-4C	
 Small Angle Grinder Adapters	4"	5/8" - 11	20,000	9005B/BZ, 9557NB/PB, 9558PB, GA4530, GA4534		743212-A
				Allows cup or wheel with 5/8"-11 arbors to fit M10 x 1.25 arbors	323015-A	
				Allows cup or wheel with 5/8"-11 arbors to fit M10 x 1.50 arbors	323016-A	

Warning: Consult owner/operator manual and adhere to all safety precautions for accessory items. Always use recommended guards. Failure to do so may result in serious injury or death from exploding wheels. Refer to ANSI B7.1 and owner/operator manual for proper accessory mounting and grinding procedures. Always wear eye protection that meets ANSI Z87.1 requirements plus a face shield wherever possible. Tools must always be properly guarded.