

EZTR50 & EZTR75 Series Residential Condensing Tankless Water Heater Specification Sheet

- **Water Connection** - top mount connections for easy water connections
- **Standard Input** - gas consumption ranges from 18,000 BTU/h to 180,000 BTU/h (EZTR50) and 199,900 BTU/h (EZTR75)
- **Capacity Range** - flow rates from 0.5 gpm up to 9.8 gpm (EZTR50) and 11.1 gpm (EZTR75)
- **Compact Design** - ANSI Z21.10.3/CSA 4.3 certified design that can be wall-mounted indoors or outdoors
- **Durable Steel Casing with Polyester Coating**
- **Heat Exchanger** - Both primary and secondary heat exchanger are manufactured with stainless steel 316L
- **Compatible with 1/2" gas pipe** - See installation manual
- **Venting Options** - Uses indoor 2" flexible polypropylene (included)
- **Direct Electronic Ignition**
- **Quick-Connect** - two identical units can be linked together by using the optional Quick Connect Cord (#QC-2) for twice the hot water capacity
- **Uniform Energy Factor** - 0.96 (NG) 0.96 (LP)
- **Temperature Controls** - includes remote thermostat that can precisely adjust the output temperature from 100°F to 140°F with the capability to display temperatures in both °C and °F
- **Power Cord Installation Kit** - 6' power cord is included
- **Safety Devices** - Flame Sensor, Overheat Prevention Device, Lightning Protection Device, Freeze Protection, and High Limit Switch
- **Additional Features** - Temperature Lockout, High Elevation Adjustment, Condensate Overflow Monitoring System, Service Reminder Function, and Wifi Ready
- **12-Year* Limited Heat Exchanger Warranty for Residential Use**
- **5-Year Limited Parts Warranty & 1-Year Reasonable Labor**
- **Approvals** - CSA, UPC**, NSF, Low NOx Approved by SCAQMD [$<14\text{ng/J}$ or 20ppm]



Included in Package

- Unit (EZ98 / EZ111)
- Flex Vent 2" Conversion Kit (EZ2-CK)
- Isolator Valves (#IK-WV-200)
- Flex Vent 2" Kit 25 Feet (EZ2FVK-1)

Optional accessory

- Flex Vent 2" Kit 35 Feet (EZ2FVK-2)



* Heat Exchanger warranty is maintained at 12 years or 6500 operational hours, whichever occurs first, when used in a single family dwelling in conjunction with a controlled recirculation system (an aquastat being the minimum pump control requirement) in accordance with the Installation Manual. Refer to the Noritz Limited Warranty for complete coverage details

** This product complies with California AB 1953 Low Lead Law and section 1417(d) of the Safe Drinking Water Act