

# Bolt Cutters



## Bolt Cutters

- Hardened alloy steel jaws are designed and manufactured to assure the longest possible blade life.
- One-step internal cam mechanism provides the quickest and simplest way to keep the cutting blades precisely aligned.
- Handles and grips designed to allow greater mechanical advantage for crisp, controlled cutting.

| Catalog No. | Model No. | Description | Capacity/Metals          |      |                            |      |                          |      | Weight |      |
|-------------|-----------|-------------|--------------------------|------|----------------------------|------|--------------------------|------|--------|------|
|             |           |             | Soft (15RC) <sup>1</sup> |      | Medium (31RC) <sup>2</sup> |      | Hard (42RC) <sup>3</sup> |      | lb.    | kg   |
|             |           |             | in.                      | mm   | in.                        | mm   | in.                      | mm   |        |      |
| 14213       | S14       | Center Cut  | 5/16                     | 7.9  | 1/4                        | 6.4  | 3/16                     | 4.8  | 1 1/4  | 1.00 |
| 14218       | S18       | Center Cut  | 3/8                      | 9.5  | 5/16                       | 7.9  | 1/4                      | 6.4  | 3 3/8  | 1.50 |
| 14223       | S24       | Center Cut  | 7/16                     | 11.0 | 3/8                        | 9.5  | 5/16                     | 7.9  | 5 7/8  | 2.70 |
| 14228       | S30       | Center Cut  | 1/2                      | 12.7 | 7/16                       | 11.0 | 3/8                      | 9.5  | 8 7/8  | 4.00 |
| 14233       | S36       | Center Cut  | 9/16                     | 14.3 | 1/2                        | 12.7 | 7/16                     | 11.0 | 13 1/2 | 6.10 |
| 14238       | S42       | Center Cut  | 11/16                    | 17.5 | 9/16                       | 14.3 | 1/2                      | 12.7 | 18 1/4 | 8.30 |

## Replacement Heads

| Catalog No. | Description       | Weight |     |
|-------------|-------------------|--------|-----|
|             |                   | lb.    | kg  |
| 18363       | S14 Head Assembly | 7/8    | 1.0 |
| 18368       | S18 Head Assembly | 1 1/4  | 1.5 |
| 18373       | S24 Head Assembly | 2 1/4  | 2.7 |
| 18378       | S30 Head Assembly | 8 7/8  | 4.0 |
| 18383       | S36 Head Assembly | 13 1/2 | 6.1 |
| 18388       | S42 Head Assembly | 18 1/4 | 8.3 |

# Cable Cutters



## No. 1380 Cable Cutter

- The Model 1380 Cable Cutter is designed to shear-cut insulated aluminum and copper cable through 1 3/8" diameter and 750 MCM\*. Drop-forged, heat-treated, alloy steel jaws shear cable with minimum distortion of internal wires. Fitted with fiberglass-insulated handles and rubber grips.

\*Not intended for cutting steel or ACSR cable.

| Catalog No. | Model No. | Description                                                  | Weight |     |
|-------------|-----------|--------------------------------------------------------------|--------|-----|
|             |           |                                                              | lb.    | kg  |
| 83350       | 1380      | Aluminum and Copper Cable through 1 3/8 Diameter and 750 MCM | 4 1/2  | 2.0 |