

Reels & Cameras



SeeSnake® microDrain™ Video Inspection System

- 1" to 3" (32 – 76 mm) lines up to 65' (20 m)*
 - Passes multiple 90° bends in most 1.5" (40 mm) drain lines.
 - SeeSnake microDrain™ video inspection system provides small size and maneuverability for small diameter and tight-turn radius inspections.
 - Lightweight and compact design is one-half the size of popular inspection systems, easily stowed in a truck and carried onto the jobsite.
 - Multi-monitor compatibility with existing SeeSnake monitors, or the micro CA-300 digital inspection camera.
 - Durable and reliable construction with hardened stainless steel camera head spring assembly for a long service life as well as long lasting high-intensity lights for exceptional viewing.
 - Ideal for inspections with tight turns such as toilet traps and P-traps.
- * 3" (76 mm) when used with a microEXPLORER or micro CA-300. 4" (100 mm) when used with a SeeSnake monitor.

Specifications

- Camera Head – 0.86" (22 mm).
- Cable Length – 65' (20 m).
- Cable Diameter – 0.33" (8.3 mm).
- Line Capacity – 1¼" to ¾" (32 - 75 / 100 mm).
- Weight – 8.6 lbs. (3.9 kg), 9.8 lbs. (4.4 kg).
- Length – 13.25" (33.7 cm).
- Width – 6.6" (16.8 cm).
- Height – 14.2" (36.1 cm).
- Resolution – 628 x 586 NTSC.
- Ball guide – 2 Included.
- Sonde – Standard with 20 m microDrain, 512 Hz.
- Counter – NA.

65' (20m) microDrain w/Sonde

Catalog No.	Description	Weight	
		lb.	kg
37468	microDrain D65S Reel (SeeSnake) (NTSC)	9.8	4.4
37473	microDrain D65S Reel (CA300) (NTSC)	9.8	4.4
40788	microDrain D65S/micro CA-300 System (NTSC)	11.1	5.0

Accessories

Catalog No.	Description	Weight	
		lb.	kg
33108	microReel Interconnect Cable for SeeSnake Monitor	0.6	0.3
33113	microReel Interconnect Cable for CA-300 Monitor	0.6	0.3
37483	microDrain D65S Drum Only NTSC	5.3	2.4
34318	microDrain Ball Guides (Standard Guide)	0.2	-
40593	microDrain Ball Guide Set (Standard + Pool)	0.2	-

(SeeSnake) = the reel containing the pushcable and camera head with a connection cable for a SeeSnake monitor
(CA-300) = the reel containing the pushcable and camera head with a connection cable for a CA-300 monitor